





www.krssdrills.in





#### **FEATURES**

DELIVERS	DEVELOPS	BULK CAPACITY	VARIABLE STROKE	
UPTO 1.5 GM / STROKE	UPTO 10,000 PSI (690 BAR)	650 GMS		





### Lever Grease Gun **Super Value**



**Pistol Grip** 

### FEATURES

DELIVERS	DEVELOPS	CAPACITY
UPTO 0.50 GM / STROKE	UPTO 5,000 PSI (345 BAR)	500 GMS <b>BULK</b> / 400 GMS CARTRIDGE



#### **FEATURES**

DELIVERS	DEVELOPS	CAPACITY
UPTO 1 GM / STROKE	UPTO 6,000 PSI (413 BAR)	500 GMS <b>BULK</b> / 400 GMS CARTRIDGE



# Mini Lever Grease Gun



### FEATURES

DELIVERS	DEVELOPS	CAPACITY
UPTO 0.55 GM / STROKE	UPTO 6,000 PSI (413 BAR)	120 CC <b>BULK</b> / 85 GMS CARTRIDGE

### Air Operated Grease Gun



FEATURES

DELIVERS	DEVELOPS	CAPACITY
UPTO 400 GM / MINUTE	UPTO 4,800 PSI (330 BAR)	500 GMS <b>BULK</b> / 400 GMS CARTRIDGE



### Mini Pistol Grease Gun - Deluxe



#### **FEATURES**

DELIVERS	DEVELOPS	CAPACITY
UPTO 0.40 GM / STROKE	UPTO 3,500 PSI (240 BAR)	120 GMS <b>BULK</b> / 85 GMS CARTRIDGE





### FEATURES

DELIVERS	DEVELOPS
UPTO	UPTO
0.90 GM /	1,000 PSI
SHOT	(69 BAR)



# Lever Grease Guns V Series



DELIVERS	DEVELOPS	CAPACITY
UPTO 1 GM / STROKE	UPTO 6,000 PSI (413 BAR)	500 GMS <b>BULK</b> I/ 400 GMS CARTRIDGE

## **19.2V Battery Powered** Grease Gun

Powerful 19.2V high torque motor

Standard 1.5Ah Ni-Cd battery pack

An additional 1.5Ah Ni-Cd battery pack for uninterrupted greasing

Automatic air release valve & bulk loader

One hour quick charger. Each battery charge provides power to dispense upto 2.4 kg grease in free flow condition

Complete with 30" high pressure hose with spring guard on both ends (prevents hose from kinking), high pressure 4 jaw coupler & 400 gm grease cartridge

Comes packed in a blow moulded case for safe storage & ease of transportation

Designed for use by mechanics, technicians, maintenance staff, farmers etc. for everyday greasing & preventive maintenance jobs.





Bucket Grease Pumps

Volume grease pump designed for quick & effortless greasing in applications requiring large volume of lubrication everyday

For use with agricultural equipment, excavators & other earth moving equipment & in automotive applications

Variable Handle Setting:

can be set for high volume or high pressure grease discharge. Pump delivers upto 9gms of grease on high volume setting. Fully CNC machined to close tolerances the pump develops upto 4,000 PSI (275 BAR) on high pressure setting

Includes follower plate

WETTED COMPONENTS Steel, Aluminium, Brass & Nitrile Rubber

**RECOMMENDED USE** NLGI 1, 2 & 3 greases

#### **FEATURES**

#### DEVELOPS

UPTO 4,000 PSI (275 BAR) ON HIGH PRESSURE SETTING

DELIVERS

UPTO 9 GM / STROKE ON HIGH VOLUME SETTING







# Foot Operated Grease Pump

High pressure portable grease pump for quick effortless greasing in everyday lubrication such as greasing of excavators & other earth moving equipment, agricultural equipment, automotive etc.

Hands free operation: Pump operates using the foot lever, which greatly reduces effort & allows high pressure greasing with highest comfort

Can be operated by hand when under low machinery

Economical:

Pump is operated by a single person & uses low cost bulk grease

Designed with all moving parts submerged in the same grease which needs to be pumped, thereby staying lubricated at all times

Moving parts create wave action in grease, auto removing air pockets & eliminating the use of a follower plate

#### FeatURes

DEVELOPS	DELIVERS
UPTO 8,700 PSI	UPTO 2 GM /
(600 BAR)	STROKE







# Air Operated Grease Ratio Pumps

World-class industrial high pressure grease pumps with guaranteed performance & hassle free opeeratio

Pump dispenses grease at pressures up to 50 times the air inlet pressure

Designed to work in tough conditions these are ideal for use in industry, workshop, farm, construction or as part off thee Mobile Grease System

All metal construction, fully CNC machined with hardened wear resistant moving parts

Reciprocating piston operated 63 mm dia. air motor

Fitted with strainer at suction tube inlet for clean grease to the bearing

Supplied complete with drum cover, rubbeer lined follower plate, 7' (84") of high pressure gre se hose, z-swivel & professional grease control valve

Portable version available with built-in steel drum, complete with wheels & pull handle

Recommended for use with light and self collapsing grease up to NLGI 2  $\,$ 

Wetted components Steel, Brass, Aluminium, Polyurethane & Nitrile Rubber

Recommended Use

Light & self collapsing grease upto NLGI 2



For use withdrums.







### BGRP/15

Portable grease pump with built-in 15 kg grease bucket

#### BGRP/30

Portable grease pump with built-in 30 kg grease bucket **BGRP/50** 

Portable grease pump with built-in 50 kg grease bucket



## Portable Greasing System Manual

Fully portable & single person operation manual greasing system designed

for volume greasing in workshop environments, site applications, on a pick-up truck, tractor, earth moving equipment etc.

Pump is operated by foot press of the spring loaded system. The hose gets charged with grease, which can then be dispensed through the Super gun fitted at the end of the hose. A single charge provides upto 30 shots of grease

Aluminium die cast super gun develops greasing pressure and has high pressure & high volume settings, actuated through a simple switch

High pressure feature is very useful to open blocked grease fittings

Pump assembly is fully sealed to prevent contamination

Pump comes complete with drum cover, rubber lined follower plate, premium ½" ID high pressure hose, super gun fitted with steel extension, coupler and 5 kg plastic grease bucket

#### Wetted components

Aluminum, Steel, Brass, Polyurethane & Nitrile Rubber



#### **FEATURES**

DEVELOPS	DELIVERS	
UPTO 10,000 PSI (690 BAR) ON	UPTO 1.25 GMS / STROKE	
HIGH PRESSURE SETTING	HIGH VOLUME SETTING	



Common sight on construction equipment requiring high volume routine greasing

#### **ORDERING INFORMATION**

CAT NR.	BUCKET	PUMP LENGTH BELOW			ATE DIMENSIONS	HOSE LENGTH
	CAPACITY	DRUM COVER	DIAMETER	O.D. STEEL END	O.D. PLATE	
GS/5	5 Kg	197 mm (7-3/4")	216 mm (8-1/2")	171 mm (6-3/4")	206 mm (8-1/8")	1.5m