

## Product Data Sheet

# MAK HYDROL TQ 32

### DESCRIPTION

This is a specially developed hydraulic transmission fluid fortified with high performance additives that incorporates excellent properties for catering to the severe demands of gears and bearings in transmission.

### PERFORMANCE BENEFITS

- Good anti-wear and anti-rust properties
- Excellent extreme pressure properties
- Useful in low temperature operating conditions

### APPLICATIONS

It is recommended for use in Turbo Transmission systems, Torque Converters & Fluid Couplings.

### PERFORMANCE LEVEL

- 3.90-8A of Voith Getreibe, Germany

Characteristics	IS 1448	Typical Figures
Density at 15° C	P:16	0.856
K.V at 40° C, cSt	P:25	32.5
Viscosity Index	P:56	118
Pour Point, °C	P:10	-45
Flash Point, (COC), °C	P:69	234
TAN, mg KOH / g	--	0.22
Color No	P:12	L 0.5

### Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

#### Bharat Petroleum Corporation Ltd.

Technical Services  
 A' Installation, Sewree (East), Mumbai – 400 015  
 Phone: 022-24176354, Fax: 022-24182511 / 24166512  
 email: z\_techservices@bharatpetroleum.in

Edition: R&D / Indl / 046 / Issue 1 / Oct, 2008