

Product Data Sheet

MAK RUSTROL 152

DESCRIPTION

It is oil based rust preventive fluid, which forms thin, tenacious oily film on the surface of the metal to be protected. The protected components can be further processed without the removal of this oil.

PERFORMANCE BENEFITS

- Contains corrosion inhibitors
- The product is compatible with general lubricating oils

APPLICATIONS

This grade is applied for protecting steel sheets and strips, metal stacks during the inter process storage period.

This grade is applied by dip or swab method.

PERFORMANCE LEVEL

- Proprietary grade

Characteristics	IS 1448	Typical Figures
Appearance	--	Light brown clear fluid
Density at 15°C	P:16	0.9146
K.V at 40° C, cSt	P:25	35.71
Viscosity Index	P:56	102
Pour point, °C	P:10	3
Flash Point, (Abel), °C	P:69	200
Copper corrosion @ 100°C for 3 hrs.	P:15	1a

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A¹ Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Indl / 113 / Issue 1 / Oct, 2008