

Product Data Sheet

MAK TEXTROL

ISO VG: 15 & 22

DESCRIPTION

These are highly refined, high viscosity index oils. They are specially recommended for ring spindles.

PERFORMANCE BENEFITS

- Possesses anti-oxidant, anti-corrosion, anti-wear and dispersant properties
- Offers resistance to rusting and corrosion

APPLICATIONS

These oils are recommended for spindle bearings of ring frames operating at very high RPM.

PERFORMANCE LEVEL

- Proprietary grade

Characteristics	IS 1448	Typical Figures	
		15	22
Appearance	--	Clear fluid	Clear fluid
Density at 15°C	P:16	0.836	0.840
K.V at 40° C, cSt	P:25	15.4	22.1
Viscosity Index	P:56	102	101
Pour Point, °C	P:10	-15	-15
Flash Point, (COC), °C	P:69	184	194
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1b	1b

Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Indl / 053 / Issue 1 / Oct, 2008