

Product Data Sheet

MAK COLD NECK GREASE

DESCRIPTION

MAK COLD NECK GREASE is calcium based grease containing bitumen and graphite.

PERFORMANCE BENEFITS

- Good tackiness
- Performs excellently even under shock load conditions

APPLICATIONS

This is used in the lubrication of steel mill roll necks during cold rolling / drawing operations.

PERFORMANCE LEVEL

- Proprietary grade

Characteristics	IS 1448	Typical Figures
Unworked penetration @ 25°C	P:60	77
Drop point, °C	P:52	105
Free Organic Acidity (as oleic acid), % by mass, max.	P:53	0.3
Free alkanity (as Ca(OH) ₂) % by mass	P:53	0.25
Water content, % by mass	P:40	1
Copper Strip Corrosion Test @ 75°C for 24 hrs.	P:51	Negative

Health and Safety

This grease is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A¹ Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Grease / 011 / Issue 1 / Oct, 2008