

Product Data Sheet

MAK BRAKE FLUID

DESCRIPTION

It is premium synthetic fluid specially developed and approved for use in hydraulic breaking systems of all vehicles.

PERFORMANCE BENEFITS

- Has a high reflux boiling point
- Good fluidity and stability even at low temperatures to make braking effective

APPLICATIONS

This oils is recommended for use in both disc and drum brake systems of vehicles.

PERFORMANCE LEVEL

- FMVSS-116 DOT-3
- IS 8654 : 2001
- SAE-J-1703

Characteristics	Requirement	Typical Figures
Appearance	Clear & Bright	Clear & Bright
Equilibrium Reflux Boiling point, (ERBP) °C, min.	205	215
Wet ERBP, °C, min.	140	152
KV, cSt at -40°C, max. at 100°C, min.	1500 1.5	1300 2.0
pH	7.0 to 11.5	8.2

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A¹ Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Auto / 036 / Issue 1 / Oct, 2008