

Product Data Sheet

MAK UNIVEX A

NLGI Grade: 2

DESCRIPTION

This is premium quality Lithium based multifunctional water resistant grease.

APPLICATIONS

This grease is recommended for use in vehicles for wheel bearings, chassis and other grease lubricated parts of automotive vehicles.

PERFORMANCE BENEFITS

- Has very good oxidation stability which ensures longer grease and component life
- Provides protection against rusting and corrosion
- Excellent thermal & structural stability
- Exhibits good water resistance property
- Has high drop point

PERFORMANCE LEVEL

- IS 12203 : 1999 Grade 1

Characteristics	IS 1448	Typical figures
Consistency of the worked grease at 25°C 60 strokes	P:60	285
Drop point, °C	P:52	192
Free Organic Acidity (as oleic acid), % by mass, max.	P:53	Nil
Free alkanity (as LiOH), % by mass	P:53	0.05
Copper Strip Corrosion Test @ 100°C for 24 hrs.	P:51	Negative

Health and Safety

This grease is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Grease / 020 / Issue 1 / Oct, 2008