

DURATIN SYNTH ROLL UP BANNER

(ES500)

Details

- Unique scratch-resistant coating eliminates the need for laminating process
- High opacity, Brilliant color & High quality image reproduction
- This multi-layer PP banner makes enforced heat resistant and flatness for indoor and outdoor with lamination.
- Cost effectiveness will be great solution having durability, tear-resistancy, and anti-curl properties..
- Certified and profiled by HP Latex Inks.

- HP Latex Certified & Profiled



Specifications

Length (ft)	100	Width (inch)	36" / 42" / 50" / 60"
Weight (gsm)	175	Coating	Resin
Caliper (mil)	8.6	Base Material	Poly Propylene
Inner Core (inch)	3	Printer	ESLUV
Surface	SATIN		

KEY FEATURES

- Unique scratch-resistant coating (Texture)
- High quality image reproduction
- Curl & Tear resistant
- For indoor and outdoor with lamination
- Instead PET roll up banner

Application

- Rollup Stands, Trade Show Panels, Indoor/Outdoor POS, Retail Aisle Banners

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.