

Super View Plus 15 INCHES



G3L

G3L Multi-Parameter Patient Monitor



G3L

Multi-Parameter Patient Monitor

Characteristics

- 15" color TFT LCD screen with multi-channel waveform display. Battery: Rechargeable high-energy built-in battery
- Advanced streamline outline design, portable, compact, Operating menu with multi-language interface selection: English, Spanish, Portuguese, Chinese, Arabic, Russian, Italian, Turkish, etc.
- Easy operation with user friendly menu structure design and rotary dial Remote control ability for long distance operation.
- Against & eliminate ESU interference & defibrillation, no need to disconnect the monitor from the patient in process of defibrillating.
- Three-application mode: monitoring, diagnosis, operating.
- WAN communication function to network with central monitoring system and make long-distance monitoring, diagnosis, maintenance and software upgrade possible
- Optional built-in wireless networking function 360 hours data storage.
- With Drug dose calculation function
- Intelligent audio and visual comprehensive alarm
- In-hospital applications include emergency room's pre and post operative care, ICU, Operation room/theater, ambulatory surgery, intermediate care/step down units, labor and delivery, and hospital-based special procedure areas.
- Suitable for use in physicians' offices, clinics, outpatient surgical centers, extended care facilities and other patient care areas, which of require affordable monitoring
- Suitable for adult, pediatrics, neonates



Specification

ECG
 Input: 3 wires /5 wires ECG cable
 Lead section: I, II, III/ I, II, III, aVR, aVL, aVF, V
 Gain(mm/mV): 1/4, 1/2, 1, 2, 4
 Sweep speed(mm/sec): 6.25, 12.5, 25, 50
 Heart rate range: 15-300 BPM
 Heart rate accuracy: ± 1%
 ST segment deviation analysis

NIBP (Non-invasive blood pressure)
 Measurement type: adult, pediatric, neonatal
 Measurement range: Systolic 4.0 - 37.0 kPa
 Diastolic 1.3 - 33.0 kPa
 Mean 2.6 - 35.0 kPa
 Accuracy: ± 0.4 kPa or 5%
 Resolution: 0.1 kPa
 Tourniquet function

Temperature (surface and rectal)
 Measurement range: 25.0-45.0 °C
 Accuracy: ± 0.1 °C
 Resolution: 0.1 °C (I, II, III selectable impedance and nasal cavity)
 response time: ≤ 3 min.
 Respiration Rate
 Measurement range: 0 - 120 BPM
 Accuracy: ± 1 BPM or 5%
 Resolution: 1 BPM

Pulse Rate
 SpO₂ measurement range: 0-100%
 Resolution: 1%
 Pulse measurement range: 30- 250BPM
 Accuracy: ± 2%
 Resolution: 1 BPM

IBP(Invasive blood pressure) (Option)
 Measurement range: -1.3~40kPa (-10~300mmHg)
 Channel: 4 channel
 Transducer sensitivity: 5MV/V/mmHg
 Unit display: KPa or mmHg selectable

ETCO₂ (main/side stream type) (Option) -Plug&Play
 Measurement range: 0-150 mmHg
 (Barometric pressure supplied by Host)
 Accuracy: 0- 40 mmHg ± 2mmHg
 41-70 mmHg ± 5% of reading
 71-100mmHg ± 8% of reading
 101-150mmHg ± 10% of reading
 Above 80 breath per minute ± 12% of reading
 Sample rate: 50ml/min
 Response time: < 3 seconds-includes transport time and rise time

Cardiac Output (Option)
 Meathod: thermodilution
 Measurement range: CO: 0.1-20.0 L/min
 TB: 23-43 °C
 TI: 0-27 °C
 Resolution: CO: 0.1 L/min
 TI: 0.1 °C
 TB: 0.1 °C
 Accuracy: CO: ± 0.2 L/min or ± 5%
 TB: ± 0.2 °C
 TI: ± 0.2 °C

Parameter output:
 Cardiac output Hemodynamics calculation

Power requirements
 Input: 100~240 V AC, 50/60Hz

Safety standard: IEC 60601-1
Quality System: ISO13485: 2003

CONCEPT IMAGING

KD-131, PITAMPURA,
 NEAR KOHAT METRO STATION, DELHI-110088
 PH: +91-9811239988 / 9312885088

WEBSITE: WWW.CONCEPTIMAGING.IN
 EMAIL: SANJEEV_CONCEPT@YAHOO.CO.IN
 INFO@CONCEPTIMAGING.IN