## Home Pride 999 Tile Adhesive



Home Pride 999 is a wonderful mixture of cement, polymer and natural mineral and other aggregate to produce adhesive when mix with water. For installation of small and medium tile on floor for interior only. It is a fantastic product in single packing with unique features and advantage. It is easy to apply and can be carried out by an ordinary labour.

### Advantage:

- Ideal for fixing ceramic tiles on floor exceed ISI type one requirement.
- ✤ It is ready to mix single component.
- Excellent Adhesion, low shrinkage.
- ✤ Need no curing, sufficient flexibility.

**Application:** Design for internal floor & application on cementitious surfaces.

Method of application: Surface should be structurally sound and free from oil, grease, white washes, paint and other loose particles, Ensure surface has normal absorption, and surface should be proper cured to avoid shrinkage cracks, remove excess water before application of tile adhesive.

**Mixing:** Content should be mixed with water as per instruction given below. Roll or shake the bag to loosen the contents, add three parts of powder to 1 part of water and mix till smooth uniform paste is formed.

**Fixing of Tile:** Apply adhesive on the surface using notched trowel and start fixing tile onto the surface and if adhesive is buttered to the tile then ensure proper

coverage of tile surface to avoid voids. Press firmly tile into adhesive to ensure good in tile bonding.

**Suitable:** Cement Mortar Bed, Cement Plaster, and Cement Terrazzo.

**Coverage:** Approximately 55-60 sq. ft. per 20kg bag with a <sup>1</sup>/<sub>4</sub> ''X <sup>1</sup>/<sub>4</sub> '' (6mm X 6mm) square notch trowel for bed of 3mm.

Packing: 20kg

**Colour:** Grey

**Certification:** ISI TYPE I

Technical Data, Tile Adhesive type I

AS per IS-15477-2004

Test Requirement	<b>Test Result</b>
------------------	--------------------

**Tensile Adhesive Strength** 

Dry condition	750 N
855 N	
Wet condition	450 N
<mark>545 N</mark>	
Shear Adhesive Str	ength (min)
Dry condition	2.5 KN
Dry condition 3.2 KN	2.5 KN
	2.5 KN
3.2 KN	2.5 KN 8 KN
3.2 KN in 24 hours	

NOTE: The data sheet subject to change without notice.

Home Pride is everybody's pride so make sure you use Home Pride.

# Home Pride 999 Tile Adhesive

Wet condition	4 KN	
5.8 KN		
Heat ageing con	dition 4 KN	5.6
KN		
Open Time	Declared by M.F.G	15
min		
Adjustability	Declared by M.F.G	15
min		
Rheology	To pass t	he
TEST		

#### Availability

#### Home Pride Adhesive Pvt.Ltd

H-533, RIICO Industrial area, Ph-I Bhiwadi,Distt. Alwar (Rajasthan)

Email: <u>homeprideadhesive@gmail.com</u>

www.homeprideadhesive.com

#### Price

Contact Home Pride Dealer in your area.

#### **Technical Services**

## Home Pride Adhesive Pvt. Ltd

H-533, RIICO Industrial area, Ph-I Bhiwadi, Distt. Alwar (Rajasthan)

NOTE: The data sheet subject to change without notice.

