

HOME PRIDE SCREED

Description

Home Pride Screed is a special polymer base mixture of natural mineral Portland cement & other fillers. It is formulated to use with water and aggregate to produce strong water retaining and self-curing Screed for interior & exterior use. It meets comprehensive, tensile and flexural strength.

Features and Benefits

- One component supplied as concentrate (Screed)
- Meets compressive, tensile & flexural strength requirement for screed.
- Water retaining, self-curing.
- Non shrinking
- Shock & impact resistant, high strength.

SUITABLE SURFACE

Cement mortar bed, cement terrazzo, concrete.

Area of Application

Designed for internal & external flooring

Mixing

Ideal mixing of water 14-16ltr for 40kg .Water can be adjusted depending on site conditions.

APPLICATION

Adjust competing according to final finish required. Immediately after application and competing of the screed adjust the

surface using a metal flattener and sort the surface using a float.

DIRECTION OF USE

Saturate and clean the surface thoroughly to remove dust and other particles. Brush the mixture firmly on the surface carefully so that the layer of the material is not too thin on the surface.

Shelf Life & Storage

12 months, store in dry & cool place

Coverage

Thickness Screed	Aggregate	Coverage
12mm	25kg	100kg 50sq.ft
25mm	25kg	125kg 30sq.ft
35mm	25kg	155kg 25sq.ft
50mm	25kg	175kg 20sq.ft

Technical Information

Properties	Result
Pot Life	½ Hour
Application Temp	40 ⁰ - 50 ⁰
Trafficable time	after 8hrs
Thickness	8-60mm

Packing

25kg

Color

Grey

CERTIFICATION

ISI TYPE I

Availability



HOME PRIDE SCREED

Home Pride Adhesive Pvt. Ltd.
H-533, RIICO Industrial area, Ph-I
Bhiwadi, Distt. Alwar (Rajasthan)

Customer Care no: 1800-11-1818
(Toll Free)

Email: homeprideadhesive@gmail.com
www.homeprideadhesive.com

Price

Contact Home Pride Dealer in your area.

Technical Services

Home Pride Adhesive Pvt. Ltd.
H-533, RIICO Industrial area, Phase-I
Bhiwadi , Distt. Alwar (Rajasthan).

Specifications subject to change without notification .Actual field performance will depend on the type of tile/stone/brick used, installation methods and site condition.

Home is everybody's pride so make sure you use Home Pride.