

WALL PUTTY

Description

HomePride Wall Putty is a single pack unique formula based on polymer, cement, chemical and waterproofing properties. For use on cement plaster on both interior and exterior walls. Due to its unique quality, it enhances the life of painted surface.

Features and Benefits

- It provides an ideal base for painting.
- It provides damp resistant smooth finish for further application of all kinds of paints. (Damp resistance means resistance to water in humid air & not physical water contacts / leakages).
- It gives pleasing look to interiors & exteriors.
- It is fine powder to be mixed with water as advised for direct application on plastered surface of the interiors / exteriors to get silky and shiny finish.
- Can be used on concrete, rendered wall, hollow block, precast walls, concrete ceilings, calcium silicate bricks & aerated light weight blocks.
- Not recommended for use on painted or other non-cementitious surfaces.

Area of Application

- To make uneven surfaces to even and smooth surfaces
- Designed for interior and exterior surfaces.

Suitable Surface

Concrete & bricks masonry, Cement mortar beds, Cement plaster, Gypsum wall board, Exterior grade plywood, Ceramic tile & stone, Cement terrazzo, Cement backer board.

Mixing

Use approximately 8 to 10 L of fresh water for 20 kg of Putty. I.e. Water to Powder ratio should be approx 40:100. Mix thoroughly till uniform and lump free paste is formed. Allow paste to loosen for 5-10 minutes. Adjust consistency if necessary. Remix and apply with putty blades.

Application

- Ensure that surface is plastered OR made with cementitious material.
- Ensure that surface is totally clean.
- Ensure that surface is moderately rough (Neither too-rough nor too-smooth).
- Ensure that surface is just-wet.
- Overwetting resulting in accumulation of water on surface should be avoided.
- Apply first coat.
- Use spatula / blade / trowel on the wall with Configuration.
- Apply second coat preferably after @ 4 hrs in hot Season & after @ 12 hrs in cold season. Second coat shall be applied to even out application marks of 1st coat, if any.
- Re-mix putty paste again for @ 1 minute, if it is left un-disturbed for @ 30 minutes.



WALL PUTTY

- Allow complete drying for @ 3 days and then use fine emery paper to remove application mark, if any

Shelf Life & Storage

6 months

Coverage

It covers approx. 16 to 20 sq.ft. per kg for 2 coats, maintaining a maximum thickness of 1.5 mm on a smooth plaster surface.

Packing

40 kg, 20kg, 5 kg, 1kg

Colour

White

Availability

Home Pride Adhesive Pvt.Ltd.

H-533, RIICO Industrial area, Phase-I
Bhiwadi, Distt. Alwar (Rajasthan).

Email: homeprideadhesive@gmail.com
www.homeprideadhesive.com

Price

Contact Home Pride Dealer in your area.

Technical Services

Home Pride Adhesive Pvt.Ltd.

H-533, RIICO Industrial area, Phase-I
Bhiwadi, Distt. Alwar (Rajasthan).

Customer Care No: 1800-11-1818
(Toll Free)

Specifications subject to change without notification. Actual field performance will depend on the type of tile/stone/brick used, installation methods and site conditions.

Home Pride is everybody's pride so make sure you use Home Pride.