

## **PRODUCTION DESCRIPTION**

It is roller or brush applied liquid polymer based waterproofing membrane for direct use under thin and thick bed installations of ceramic tile, stone and other finishes. It is recommended for residential and commercial floor and wall installation.

## **FEATURES**

- It protects gypsum board, cementitious board and concrete against water penetration under long-term weathering.
- Highly durable and economical.
- Easily brush applied.
- Membrane up to 3mm bonds directly to copper steel and PVC plumbing fixtures.
- Fast drying, flood test can allowed after 24 hours.
- It can be used for both, internal and external application.

**APPLICATION:** Kitchen, bathroom, swimming pool, fountain water bodies, shower pans, stall and tub, spa and hot tubs, terrace gardens and balconies over unoccupied space, facade etc.

**ADVANTAGE:** Fast and easy to install applies like paint, water cleanable, Non flammable.

**SUITABLE SURFACE:** Concrete & bricks masonry, Cement mortar beds, Cement plaster, Gypsum wall board, Exterior grade plywood, Ceramic tile & stone, Cement terrazzo, Cement backer board.

## **TECHNICAL DATA**

Pot Life	30 minutes
Application	
Temperature	25-35 deg
Re coat able	Yes
Tensile Strength	450psi (3.1 Mpa)
Elongation	<400%
Colour	Grey/Black
Dry Time	Approx. 2-3 hrs 1 <sup>st</sup> coat
Cure Time	Approx. 3-4 hrs 2 <sup>nd</sup> coat
Full Cure	Approx. 5-7 days

**SHELF LIFE:** 6 months

**COVERAGE:** Approx. 200-225sq ft./20ltr pail.

**PACKAGING:** 5ltr&20ltr pails

## **APPLICATION METHOD**

- Saturate and neatly clean the surface to remove dirt, dust, loosely attached particles and bond inhibiting compounds.
- It is a ready to use product .Just stir and apply
- After applying allow it to stand for 5 minutes before it to mature.
- Brush the product firmly on to the primed surface. Care must be taken not to spread the material too thin on the surface
- Allow atleast 2-4 hours to cure before applying subsequent coats.

Note: Membrane reinforcing fabric for coves, corners and board joints is sold separately.

Fabric roll packing: width -15cm and length -18m to 25m.

**Home Pride is everybody's pride so make sure you use Home Pride.**

# HOME POLY PRIDE 9001 MEMBRANE



## *Availability*

**Home Pride Adhesive Pvt.Ltd**  
H-533, RIICO Industrial area, Ph-I  
Bhiwadi, Distt. Alwar (Rajasthan)

**Email:** [homeprideadhesive@gmail.com](mailto:homeprideadhesive@gmail.com)

[www.homeprideadhesive.com](http://www.homeprideadhesive.com)

## *Price*

Contact Home Pride Dealer in your area.

## *Technical Services*

**Home Pride Adhesive Pvt. Ltd.**  
H-533, RIICO Industrial area, Phase-I  
Bhiwadi , Distt. Alwar (Rajasthan).

**HEALTH & SAFETY: HOME POLY PRIDE 9001 MEMBRANE** is non –toxic. Use of gloves and goggles is recommended. Any splashes to skin or eyes should be waste off with clean water. In the event of prolonged irritation, medical advice should be sought. **HOME PRIDE** components are non-flammable.

**Specifications subject to change without notification .Actual field performance will depend on the type of tile/stone/brick used, installation methods and site conditions**

*Home Pride is everybody's pride so make sure you use Home Pride.*