

HOME PRIDE SHIELD STONE SEAL

Description

Home Pride Shield Stone Seal is a polymer and chemical based single component solution which penetrates that protects extra porous stone such as fine grain marble, granite, sandstone, Lime stone and other synthetic stones. The unique formulation provides water repellency as well as oleo phobic i.e. oil repellent properties for concrete, grouts. The treated pores of the surface from an invisible barrier allowing the vapour diffusion due to penetrating effect. It set to form hard wearing film while maintaining natural colour of stone and tile.

Features & Benefits

- Used for even low porous stone & marble.
- Easy to apply using brush, sponge or cloth.
- It can be applied for both external & internal application.
- Highly durable & economical.
- Ready to use no dilution required at site.
- Superior coverage

Area of Application

Designed for internal floor application. It is recommended for application on cementitious substrates, self-leveling screeds.

Application

- Surface should be clean, dry free of contamination e.g. oil, dust, grease, etc.
- New surface need to dry 48-72 hours before application of sealer.

- Apply evenly, over surface with a paint brush, clean cloth or sponge. Care must be taken not to apply too thick or lumpy coats.
- Allow it to penetrate for 5-15 minutes and wipe the surface with dry clean cloth or sponge after application. Any excess material needs to be wiped off.
- Inter-coat must be done wet on wet condition before first coat gets fully cured.
- Allow 24 – 48 hours for air cure to develop hydrophobic & oleo phobic effects.
- Preliminary testing on small trial area is important to determine the compatibility & possible discoloration of the surface to be treated.
- Do not apply on damp or wet surfaces; avoid application during wet weather conditions & on to surfaces that are extremely hot.
- If applied on damp or wet surface, it is likely to peel.
- Immediately clean hands with soap and water after application.

Suitable Surface

Natural stones, Synthetic marbles, Sand stones, Marble Granites, Travertine, Concrete, Fibrous cement material, Bricks, Unglazed Tile, Masonry, Flamed, Honed, Finished granite & Stones and Pavers.

TECHNICAL SPECIFICATION

Appearance	Light Yellowish
Density @25°C	0.86 +/- gm/cc



HOME PRIDE SHEILD STONE SEAL

Shelf Life & Storage

6 months from the date of manufacturing.

Coverage

Approximately 25-500 sq.ft/ltr. Depending on the porosity level of the surface.

Packing

1Ltr, 5ltr & 20ltr

Colour

Yellowish Transparent

Availability

Home Pride Adhesive Pvt. Ltd.

H-533, RIICO Industrial area, Phase-I
Bhiwadi , Distt. Alwar (Rajasthan).

Email: homeprideadhesive@gmail.com
www.homeprideadhesive.com

Price

Contact Home Pride Dealer in your area.

Technical Services

Home Pride Adhesive Pvt. Ltd.

H-533, RIICO Industrial area, Phase-I
Bhiwadi , Distt. Alwar (Rajasthan).

Customer Care No: 1800-11-1818
(Toll Free)

Note: for application on any other substrate that is mentioned above, please contact Home Pride Personnel for technical assistance on our Toll Free helpline number

Specifications subject to change without notification .Actual field performance will depend on the type of tile/stone/brick used, installation methods and site conditions.

Home is everybody's pride so make sure you use Home Pride.