



URJA SEALANTS PVT LTD

Technical Data Sheet

URJA BODY SEALANT

TDS No:0012013

Date : 1 Jan , 2013

Description: URJA BODY SEALANT is a high-quality multipurpose non-sag Acrylic sealant that on exposure to atmosphere and humidity to form a durable elastomeric. URJA BODY SEALANT is manufactured in strict quality assurance systems and with the responsible care program.

Chemical base	1-C Polyurethane	
Color	Off White	
Appearance	Thixotropic Paste	
Cure Mechanism	Air Drying	
Curing Speed	4 mm/24 hours	
Density (Uncured)	1.4	
Non-Sag Properties	Good	
Application temperature	5°C to 40°C	
Shore A-hardness	58-59 approx.	
Tensile Strength	14.3 Kg/cm ²	
Service temperature Short term	Permanent	5°C to 90°C
	1 day	120°C
	1 hour	140°C

Stoage : To be Stored indoors away from direct sunlight, heat source and moisture.

Application: Surface should be pretreated / primed. Urja Body Sealant can be applied by gun, spatula or brush

Shelf Life: Four months under above conditions

Packing: 310ml cartridge / Kg in M/S drum/ plastic drum.

Note:

The company's products are sold subject to the Company's standard terms and conditions of sale. Products are warranted against defective materials and workmanship. The company makes every effort to ensure that all the information, recommendations or the specifications provided by it are accurate and true. However as the company has no control over the conditions of use, it cannot accept any liability, either directly or indirectly regarding the usage of its products. Product specifications are subject to change without prior intimation to users as the products are being