



URJA SEALANTS PRIVATE LIMITED

TECHNICAL DATA SHEET URJA WATER BASE DUCT SEALANT

Description:

URJA WATER BASE DUCT SEALANT is a fast setting, elastomeric water base joint sealant for low medium & high velocity heating & air conditioning ducts. It has very good adhesion to galvanize, aluminum or mild steel metal ducts. It gives good flexible seal against air leakages and do not require reinforcing tapes or mechanical fasteners.

URJA WATER BASE DUCT SEALANT is suitable for Cleanroom and Pharmaceutical Projects.

It passes the Flammability test as per **UL94 HB class test** when tested at **ARAI, lab, pune**.

Also it is food grade material when tested as per **IS & USFDA test method** at **FOOD HYGENE & HEALTH LABORATORY**.

Typical Properties:

Colour	: White / Grey / Black /clear
Viscosity	: 800 to 1200 cps.
Curing Schedule	: (25°C) and 50% R H.
Set to Touch: 1 hour, dry through	: 1 Hrs Dry.
Wet Flammability (ASTM D 3278)	: No flash at 99° C
Non Volatile content	: 85 %
Specific Gravity	: 1.56/1.05

Storage: Store in a cool and dry place away from direct sunlight. Storage below 18°C to 23°C is recommended

Application: Apply by brush, cartridge gun, trowel or extrusion. On spiral duct apply a thick coat of URJA water base duct sealant. Brush excess URJA Water base duct sealant over the exterior of the joint and over the heads of all metal screws after they are in place and the joints are mechanically fastened.

Shelf Life: 9 months under above conditions

Packing: 310ml cartridge

Note:

The company's products are sold subject to the Company's standard terms and conditions of sale. Products are warranted against defective materials and workmanship. The company makes every effort to ensure that all the information, recommendations or the specifications provided by it are accurate and true. However as the company has no control over the conditions of use, it cannot accept any liability, either directly or indirectly regarding the usage of its products. Product specifications are subject to change without prior intimation to users as the products are being.