



Approx Performance Chart at 2800 RPM, 415 Volts, 50 Hz Supply,  
S.S. Motor Body & C.I. Bowl & S.S. 410 Impeller,  
(Suitable For 125mm Bore Dia) Submersible Pump Sets.



Maxl. Head Per Stage - 35 Feet

AP5M-100				Price ₹		Discharge In L.P.M.							
Model No.	H.P.	STG.	Outlet	Only Pump	Pump Set	680	620	550	480	400	250	120	0
AP5M-10033	3.0	3	2.5"	6210/-	26000/-	6	9	12	15	18	21	24	27
AP5M-10044	4.0	4	2.5"	7540/-	29060/-	8	12	16	20	24	28	32	36
AP5M-10055	5.0	5	2.5"	8870/-	31910/-	10	15	20	25	30	35	40	45
AP5M-10066	6.0	6	2.5"	10200/-	35850/-	12	18	24	30	36	42	48	54
AP5M-100758	7.5	8	2.5"	12860/-	40920/-	16	24	32	40	48	56	64	72
AP5M-1001010	10.0	10	2.5"	15520/-	46900/-	20	30	40	50	60	70	80	90

Total Head in Meters

Maxl. Head Per Stage - 35 Feet

AP5M-125				Price ₹		Discharge In L.P.M.							
Model No.	H.P.	STG.	Outlet	Only Pump	Pump Set	670	620	565	495	420	265	170	0
AP5M-12543	4.0	3	2.5"	6210/-	27730/-	9	12	15	18	21	24	27	30
AP5M-12554	5.0	4	2.5"	7540/-	30580/-	12	16	20	24	28	32	36	40
AP5M-12565	6.0	5	2.5"	8870/-	34580/-	15	20	25	30	35	40	45	50
AP5M-125756	7.5	6	2.5"	10200/-	38260/-	18	24	30	36	42	48	54	60
AP5M-125108	10.0	8	2.5"	12860/-	44240/-	24	32	40	48	56	64	72	80

Total Head in Meters

