

Automatic Multi Head ROPP Cap Sealing Machine

TECHNICAL SPECIFICATION

Model		GT-ARCS - 100	GT-ARCS - 150	GT-ARCS - 200
Output/Hour*		3600 to 6000 Bottles	3600 to 9000 Bottles	4000 to 12000 Bottles
Direction of Movement		Left to Right		
No. of Heads		4 Nos.	6 Nos.	8 Nos.
Electrical Specifications**	Main Motor	1.5 HP / 415 Volts / 50 Hz.		2 HP / 415 Volts / 50 Hz.
	Cap Feeding Bowl	0.25 HP / 415 Volts / 50 Hz.		
Height of Conveyor**		860mm to 910mm		

SALIENT FEATURES :

- No container no cap arrangement.
- S.S. elegantly Matt finished body.
- Adjustable height of conveyor belt, to align with other machines of the line.
- Sealing pressure can be varied to suit different gauges and size of caps.
- Low noise level, low power consumption.
- Self lubricating UHMW-PE guide profile for SS slat chain provides low friction wear surface, smooth and noiseless conveying.
- S.S. cladding or hard chrome plating of all exposed parts to ensure long life and resistance against corrosion.
- Universal coupling for quick and easy setting of In-feed worm.
- Adjustable bottle height gauge for easy and quick setting.