











## SIMPLEX FLAT WEBBING SLINGS

### FEATURES

- 100% High Tenacity Polyester
- Made of single thickness of Webbing
- Flat & wide load bearing surface
- According to EN-1492-1:2000
- ASME B 30.9 & IS:15041
- Safety Factor 7:1 and 5:1
- Low Elongation 3 – 7%
- High strength to weight ratio
- Available up to 300 mm width
- Colour coded for easy identification
- Maximum working temperature 90° c
- Anti-abrasion sleeves and anti cutting sleeves protection (optional)

			SIMPLEX WEBBING SLINGS CAPACITY IN KGS									
			WLL in kg with one webbing sling					WLL in kg with two webbing slings				
			Straight lift	Choke Hitch	Basket Hitch			Straight Inclination		Choke Inclination		
up to 7°	7° - 45°	45° - 60°			7°-45°	45° - 60°	7°-45°	45° - 60°				
ITEM CODE	WIDTH	COLOUR CODE										
MODE FACTOR			M=1.0	M=0.8	M=2	M=1.4	M=1.0	M=1.4	M=1.0	M=1.12	M=0.8	
LSP-500	25	VIOLET	500	400	1000	700	500	700	500	560	400	
LSP-1000	50	GREEN	1000	800	2000	1400	1000	1400	1000	1120	800	
LSP-1500	75	YELLOW	1500	1200	3000	2100	1500	2100	1500	1680	1200	
LSP-2000	100	GREY	2000	1600	4000	2800	2000	2800	2000	2240	1600	
LSP-2500	125	RED	2500	2000	5000	3500	2500	3500	2500	2800	2000	
LSP-3000	150	BROWN	3000	2400	6000	4200	3000	4200	3000	3360	2400	
LSP-4000	200	BLUE	4000	3200	8000	5600	4000	5600	4000	4480	3200	
LSP-5000	250	ORANGE	5000	4000	10000	7000	5000	7000	5000	5600	4000	
LSP-6000	300	ORANGE	6000	4800	12000	8400	6000	8400	6000	6720	4800	