











# Triplex Flat Slings

## FEATURES

- 100% High Tenacity Polyester
- Made of **3 Ply** Webbing
- Flat & wide Load bearing surface
- According to EN-1492-1:2000 or ASME B 30.9, IS:15041
- Safety Factor 7:1 and 5:1
- Low Stretch Factor: Elongation 3-7%
- High strength to weight ratio: Weight 80% less than Equivalent Wire or Chain slings
- Available up to 300 mm width & **18 Ton** Capacity
- Colour coded for easy identification
- Maximum working temperature 90° c
- Anti-abrasion sleeves and Anti-cutting sleeves protection (optional)



			TRIPLEX WEBBING SLINGS CAPACITY IN KGS								
			WLL in kg with one webbing sling					WLL in kg with two webbing slings			
			Straight lift	Choke Hitch	Basket Hitch			Straight Inclination		Choke Inclination	
up to 7°	7° - 45°	45° - 60°			7°-45°	45°- 60°	7°-45°	45°- 60°			
ITEM CODE	WIDTH	COLOUR CODE									
MODE FACTOR			M=1.0	M=0.8	M=2	M=1.4	M=1.0	M=1.4	M=1.0	M=1.12	M=0.8
LTP-1500	25	VIOLET	1500	1200	3000	2100	1500	2100	1500	1680	1200
LTP-3000	50	GREEN	3000	2400	6000	4200	3000	4200	3000	3360	2400
LTP-4500	75	YELLOW	4500	3600	9000	6300	4500	6300	4500	5040	3600
LTP-6000	100	GREY	6000	4800	12000	8400	6000	8400	6000	6720	4800
LTP-7500	125	RED	7500	6000	15000	10500	7500	10500	7500	8400	6000
LTP-9000	150	BROWN	9000	7200	18000	12600	9000	12600	9000	10080	7200
LTP-12000	200	BLUE	12000	9600	24000	16800	12000	16800	12000	13440	9600
LTP-15000	250	ORANGE	15000	12000	30000	21000	15000	21000	15000	16800	12000
LTP-18000	300	ORANGE	18000	14400	36000	25200	18000	25200	18000	20160	14400