


Quadruplex Flat Slings

FEATURES

- 100% High Tenacity Polyester
- Made of **4 Ply** Webbing
- Flat & wide Load bearing surface
- According to EN-1492-1:2000 or ASME B 30.9, IS:15041
- Safety Factor 7:1 and 5:1
- Low Stretch Factor: Elongation 3-7%
- High strength to weight ratio: Weight 80% less than Equivalent Wire or Chain slings
- Available up to 300 mm width & **24 Ton** Capacity
- Colour coded for easy identification
- Maximum working temperature 90°C
- Anti-abrasion sleeves and Anti-cutting sleeves protection (optional)



			QUADRIPLEX WEBBING SLINGS CAPACITY IN KGS									
			WLL in kg with one webbing sling					WLL in kg with two webbing slings				
			Straight lift	Choke Hitch	Basket Hitch			Straight Inclination		Choke Inclination		
ITEM CODE	WIDTH	COLOUR CODE										
MODE FACTOR			M=1.0	M=0.8	M=2	M=1.4	M=1.0	M=1.4	M=1.0	M=1.12	M=0.8	
LQP-2000	25	VIOLET	2000	1600	4000	2800	2000	2800	2000	2240	1600	
LQP-4000	50	GREEN	4000	3200	8000	5600	4000	5600	4000	4480	3200	
LQP-6000	75	YELLOW	6000	4800	12000	8400	6000	8400	6000	6720	4800	
LQP-8000	100	GREY	8000	6400	16000	11200	8000	11200	8000	8960	6400	
LQP-10000	125	RED	10000	8000	20000	14000	10000	14000	10000	11200	8000	
LQP-12000	150	BROWN	12000	9600	24000	16800	12000	16800	12000	13440	9600	
LQP-16000	200	BLUE	16000	12800	32000	22400	16000	22400	16000	17920	12800	
LQP-20000	250	ORANGE	20000	16000	40000	28000	20000	28000	20000	22400	16000	
LQP-24000	300	ORANGE	24000	19200	48000	33600	24000	33600	24000	26880	19200	

