











MULTIPLY FLAT POLYESTER SLINGS

FEATURES

- 100% High Tenacity Polyester
- Made of multi-layered Webbing
- Flat & wide Load bearing surface
- According to EN-1492-1:2000 or ASME B 30.9
- Safety Factor 7:1 and 5:1
- Low Stretch Factor: Elongation 3-7%
- High strength to weight ratio
- Available up to 300 mm width & 110 Ton Capacity
- Colour coded for easy identification
- Maximum working temperature 90°C



			FLAT MULTY PLY WEBBING SLINGS CAPACITY IN KGS								
			WLL in kg with one webbing sling					WLL in kg with two webbing slings			
			Straight lift	Choke	Basket Hitch			Straight Inclination		Choke Inclination	
up to 7°	7° - 45°	45° - 60°			7°-45°	45° - 60°	7°-45°	45° - 60°			
ITEM CODE	WIDTH	COLOUR CODE									
MODE FACTOR			M=1.0	M=0.8	M=2	M=1.4	M=1.0	M=1.4	M=1.0	M=1.12	M=0.8
LMP-36	300	ORANGE	36000	28800	72000	50400	36000	50400	36000	40320	28800
LMP-48	300	ORANGE	48000	38400	96000	67200	48000	67200	48000	53760	38400
LMP-50-10	250	ORANGE	50000	40000	100000	70000	50000	70000	50000	56000	40000
LMP-50	300	ORANGE	50000	40000	100000	70000	50000	70000	50000	56000	40000
LMP-60	300	ORANGE	60000	48000	120000	84000	60000	84000	60000	67200	48000
LMP-72	300	ORANGE	72000	57600	144000	100800	72000	100800	72000	80640	57600
LMP-84	300	ORANGE	84000	67200	168000	117600	84000	117600	84000	94080	67200
LMP-100	300	ORANGE	100000	80000	200000	140000	100000	140000	100000	112000	80000
LMP-110	300	ORANGE	110000	88000	220000	154000	110000	154000	110000	123200	88000





Sling can fail or be damaged, misused or overloaded, Inspect before each use. Damaged sling shall not be used. Use only if trained. Do not exceed the rated capacity, Protect the sling from being cut by load edges, sharp corners, protrusions and abrasive surfaces, Avoid exposure to acid, alkali and temperature over 180 deg F. DEATH OR INJURY can occur from improper maintenance