MULTILEG POLYESTER SLINGS

Multi leg Polyester slings are made of using either Flat Webbing Slings Straps or Endless type round slings as per specific requirements depending upon uses and safe working loads. A set of multi leg slings includes Master link, Auxiliary links and different end fittings like Eye hooks, Swivel hooks, D-Shackles or Bow- Shackles, Rings as required. All these fittings are made of quenched and tempered alloy steel grade-80 material. Flat slings are stitched directly to the metal ring while Endless round slings are attached with connecting links. Anti-abrasive and Anti-cutting protection sleeves can be fitted as per specific requirements.



FEATURES

SELECTION OF FLAT WEBBING OR ROUND SLINGS.
CHOICE OF 2 LEG, 3 LEG AND 4 LEG TYPES
AVAILABLE IN CUSTOMISED LENGTHS
HIGH STRENGTH TO WEIGHT RATIO
COLOUR CODED FOR IDENTIFICATION
DIFFERENT END FITTINGS AVAILABLE
END FITTING METAL COMPONANTS FORGED ALLOY STEEL
ANTI-ABRASION SLEEVES AND ANTI CUTTING SLLEVES PROTECTION
Conforms EN-1492-1, En-1492-2 and ASME B30.9

ADVANTAGE

Better load control and balance. Bridle slings give fixed lifting points and choice of multiple legs.

Hardwares avoid wearing & cuts of slings at load bearing points.

| FERRETE | THE CONTRACT OF THE CONTRACT O |
|-------------|--|
| RETERRO PRO | |
| 1 | |

| | COLOUR | MULTI LEG SLING CAPACITY AT 90° | | | |
|-------|--------|---------------------------------|-------------|-------------|--|
| WIDTH | | SWL | SWL | SWL | |
| | | 2 LEG SLING | 3 LEG SLING | 4 LEG SLING | |
| MM | | TON | TON | TON | |
| 25 | VIOLET | 1.4 | 2.1 | 2.8 | |
| 50 | GREEN | 2.8 | 4.2 | 5.6 | |
| 75 | YELLOW | 4.2 | 6.3 | 8.4 | |
| 100 | GREY | 5.6 | 8.4 | 11.2 | |
| 125 | RED | 7.0 | 10.5 | 14.0 | |
| 150 | BROWN | 8.4 | 12.6 | 16.8 | |
| 200 | BLUE | 11.2 | 16.8 | 22.4 | |
| 250 | ORANGE | 14.0 | 21.0 | 28.0 | |
| 300 | ORANGE | 16.8 | 25.2 | 33.6 | |



