

ROTARY FORMING & ROTARY SEALING BLISTER PACKAGING MACHINE

Models : HC - BLISS 150 | 150 XL | 150 ARROW | 150 ARROW XL



OPTIONAL FEATURES :

- PERFORATION
- BATCH CODE LETTER EMBOSSING ATTACHMENT
- PRINT REGISTRATION CONTROL FOR PACK TO PRINT
- PLC BASED OPERATION
- INKJET PRINTER



TECHNICAL SPECIFICATION

DESCRIPTION	PVC BLISTER - 150
Base Film Width Max.	120 MM
Base Film Thickness Max.	0.25 -0.4 MM
Base Film Material	PVC / PVDC / ACLAR / OPAQUE / TRIPLEX
Sealing Foil Width Max.	116 MM
Sealing Foil Thickness Max.	0.02 - 0.04 MM
Sealing Foil Material	Aluminum / CR Foil / Laminated Paper
Pack Length	110 MM
Pack Width	100 MM
Forming Depth	16 MM
Max. Output	upto 600000 Tablet - Capsules per shift(8 Hr.)
Cutting Speed	upto 70 Strokes per/min. for Tablet-Capsules
Electrical Input	3 Phase, 3 KW, 50 Hz, 5 Wire, 2.5 Sq. MM
Machine Dimensions (L X W X H)	2000 X 1000 X 1600 MM
Compressed Air Requirement	
CFM	15 CFM
Pressure	6 bar
Chilled Water Requirement	100 Liters of chilled Water / Hour at 16° C Temperature
Additional Safety	Air Dryer, Voltage Stabilizer