

Plug Valves

- Standard service is used up to 15,000psi and tested at 22,500psi
- H2S service is used up to 10,000psi and tested at 15,000psi
- Rugged Construction with Forged Alloy Steel Body
- Reliable Performance at high working pressure
- Bottom Entry design, Top Entry design, Easy Maintenance
- Valve Parts are Interchangeable with most major designs
- Suitable for variety of high pressure applications such as fracturing, cementing, acidizing and etc.
- Each valve is serialized
- MTR and Test Report are available at any time



Plug Valve

NO	Item	Q'ty
Ass'y	Plug Valve 1502 HandleType	1
1	Cap Screw	2
2	Washer 1(Small)	2
3	Washer 2(Bigger)	2
4	Handle Adapter	1
5	Stop Bolt	1
6	Stop Collar	1
7	Grease Fitting	1
8	Body	1
9	Wing Nut	1
10	Segment	3
11	Retainer Ring	1
12	Lip Seal	1
13	Plug Seal	2
14	Plug	1
15	Roll Pin	2
16	Insert	2
17	Insert O-ring	2
18	Adjusting Nut O-ring	1
19	Adjusting Nut	1



Plug Valve Repair Kit

NO	Item	Q'ty
-	Repair kit Set	-
13	Plug Seal	2
14	Plug	1
16	Insert	2
17	Insert O-ring	2
18	Adjusting Nut O-ring	1

Seal Kit Contains No. 13, 17 and 18.

Size	End Connection	Service	Working Pressure	Test Pressure	Operation type	Dimensions (Inch)				
						A	B	C	D	E
2x1	1502 Mx F	Standard	15,000	22,500	Handle	10.53	4.74	4.50	4.50	1.00
		H ₂ S	10,000	15,000						
2x2	LP Thread	Standard	10,000	15,000	Handle	8.50	5.41	5.25	6.85	2.05
	1502 Mx F	Standard	15,000	22,500						
		H ₂ S	10,000	15,000						
	13.88	5.41	5.26	6.85						
3x3	1502 Mx F	Standard	15,000	22,500	Gear	17.00	7.20	-	9.06	3.05
		H ₂ S	10,000	15,000	Handle					

* Each size can be changed as customer's requirements.