

## SANDEEP THREE HEAD MULTI BORING

## **MODEL MZ 7321A**



**SALIENT FEATURES:** 

1.	PLC Control, ensures perfect operation as set. The Digital display touch screen incorporates a
	counting meter to show number of pieces / cycles that machine has worked. Choice of
	drilling vertical or horizontal first on the touch screen.
2.	Three Head Multi Boring Machine has one Single Horizontal Drilling Head and Two Vertical
	Drilling heads which can be adjusted to the desired distance from the fence. The locking of

vertical heads in pneumatic. A support fend	e 2mt long is provided to	hold wide panels and
---	---------------------------	----------------------

has 4 stoppers on its scale.



## ${\it 3.} \quad \hbox{Digital Electric Display Meter displaying 1/10th of millimeter}$

is showing exact distance of the Drill position of the Vertical &

Horizontal heads from the fence. A scale with pointer & light is

also provided on the Vertical scale on the horizontal head is a

	mechanical digital readout also to set the height of the drilling	
	head.	
4.	An Emergency switch operated through a long rope	
	is fitted on the Top of the machine so that it can be used from	

other	side	of the	machine	when	desired
Juici	Siuc	or are	macmin	WITCH	ucsii cu.



5. Two collets cage / stand are provided to keep Extra

collets with drills in either side of the machine.

Which are not being used and avoid breaking of the drill bits

due to falling from the machine.

Gentral Circuit Pierre

The Control States

Th

 ${\bf 6.} \quad \textbf{The Electrical Circuit diagram of Machine is pasted}$ 

inside of the Electric Panel Door.

7.	A cabinet is provided on the right side of the machine to keep machine Manual; Tools; Drills
	collets etc.

8.	Accuracy of Machining ±0.2mm
9.	6 Nos. Collets are provided with each drilling head along with Tool Box.
	Drill bits for demonstration are provided free of cost.

TECHNICAL SPECIFICATION	IS:
Maximum Drilling Dia	35mm (Single Head)
	13mm (Two Heads)
Maximum Drilling Depth	60mm

10. A lubrication pump is provided to give oil to all desired places.

Maximum Center	
Distance Between vertical	L Max. x W Max = 1350mm x 640mm
Holes	
Minimum Center	L Min. x W Min = 135mmx 32mm
Distance Between Holes	

Adjustable 2mt long with 4 length stops.

Support fence

Total Number of

 $21 \times 3 = 63$ 

**Drilling Spindle** 

**Installation Pitch of** 

10mm

**Drilling Head** 

Spindle Speed

2840 rpm

Air Pressure

0.5 – 0.6 mpa

Total Motor Power 4.5 KW

Weight 875 Kg

Overall Dimensions 2450 x 2500 x 1570mm (Approx.)

https://www.youtube.com/watch?v=8L74cJ2to-I

