

S. NO.	RF Cable	PART NO.	DESCRIPTION	IMAGES
1	1-1/4" CABLE	ST01114LDF06	Flex Cable Impedance - 50ohm Colour - Black Inner Conductor-Smooth Copper Tube -13.10mm Dielectric-Foamed Polyethylene-32.50mm Outer Conductor-Annularly Corrugated Tube-35.80 Jacket-Flame Retardant Jacket- 39.00mm	
2	1/2" LDF CABLE	ST0112LDF06	Flex Cable Impedance - 50ohm Colour - Black Inner Conductor-Copper-clad Aluminum Wire -4.80mm Dielectric-Foamed Polyethylene-12.50mm Outer Conductor-Annularly Corrugated Tube-13.80mm Jacket-Black Low Smoke Halogen-Free Flame Retardant Polyolefin- 15.80mm	
3	1/2" SF CABLE	ST0112SF06	Super Flex Cable Impedance - 50ohm Colour - Black Inner Conductor-Copper-clad Aluminum Wire -3.56mm Dielectric-Foamed Polyethylene-9.00mm Outer Conductor-Annularly Corrugated Tube-12.19mm Jacket-Black Low Smoke Halogen-Free Flame Retardant Polyolefin- 14.70mm	
4	1/4" LDF CABLE	ST0114LDF06	Flex Cable Impedance - 50ohm Colour - Black Inner Conductor-Copper clad aluminium -2.70mm Dielectric-Foamed Polyethylene-6.45mm Outer Conductor-Annularly Corrugated Tube-7.9mm Jacket-Black - 8.82mm	
5	1/4" SF CABLE	ST0114SF06	Super Flex Cable Impedance - 50ohm Colour - Black Inner Conductor-Copper clad aluminium -1.90mm Dielectric-Foamed Polyethylene-4.70mm Outer Conductor-Annularly Corrugated Tube-6.40mm Jacket-Black - 7.40mm	
6	1-5/8" CABLE	ST01158LDF06	Flex Cable Impedance - 50ohm Colour - Black Inner Conductor-Helix Corrugated Copper Tube -17.30mm Dielectric-Foamed Polyethylene-43.00mm Outer Conductor-Annularly Corrugated Tube-46.50mm Jacket-Black Low Smoke Halogen Free Flame Retardant Polyolefin- 49.80mm	
7	7/8" ALUMINUM CABLE	ST0178AL06	Flex Cable Impedance - 50ohm Colour - Black Inner Conductor- Corrugated Copper Tube -9.1mm Dielectric-Foamed Polyethylene-22.5mm Outer Conductor-Corrugated Aluminium Tube-24.8mm Jacket-Black PE- 27.5mm	
8	7/8" COPPER CABLE	ST0178CU06	Flex Cable Impedance - 50ohm Colour - Black Inner Conductor- Corrugated Copper Tube -9.1mm Dielectric-Foamed Polyethylene-22.5mm Outer Conductor-Corrugated Aluminium Tube-24.5mm Jacket-Black PE- 27.5mm	

<p>9 7/8" Radiation Leaky Cable</p>	<p>ST0178RLC06</p>	<p>Flex Cable Impedance - 50ohm Colour - Black Inner Conductor- Copper Tube -9.0mm Dielectric-Physical Foamed PE - 22.8mm Outer Conductor-Copper Foil - 24.0mm Jacket-Black LSZH - 27.2mm</p>	
<p>10 1-1/4 " Radiation Leaky Cable</p>	<p>ST01114RLC06</p>	<p>Flex Cable Impedance - 50ohm Colour - Black Inner Conductor- Helical Copper Tube -13.8mm Dielectric-Physical Foamed PE - 33.2mm Outer Conductor-Copper Foil - 34.0mm Jacket-Black LSZH - 37.6mm</p>	
<p>11 1-5/8 " Radiation Leaky Cable</p>	<p>ST01158RLC06</p>	<p>Flex Cable Impedance - 50ohm Colour - Black Inner Conductor- Helical Copper Tube -17.3mm Dielectric-Physical Foamed PE - 43.2mm Outer Conductor-Copper Foil - 44.2mm Jacket-Black LSZH - 48.0mm</p>	