











S. NO.	RF Cable	PART NO.	DESCRIPTION	IMAGES
1	HLF 100 Cable	ST01HLF10006	Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Copper Clad Steel - 0.45mm Dielectric- Solid PE - 1.54mm Inner Shield - Unsealed APA Tape - 1.65mm Outer Shield - 38AWG, 90% Tinned Copper Braid - 2.05mm Jacket - Black PE - 2.79mm	
2	HLF 195 Cable	ST01HLF19506	Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Solid Bare Copper - 0.94mm Dielectric- Foamed PE - 2.79mm Inner Shield - Unsealed APA Tape - 2.95mm Outer Shield - 36AWG, 95% Tinned Copper Braid - 3.50mm Jacket - Black PE - 4.95mm	
3	HLF 200 Cable	ST01HLF20006	Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Solid Bare Copper - 1.12mm Dielectric- Foamed PE - 2.95mm Inner Shield - Unsealed APA Tape - 3.12mm Outer Shield - 36AWG, 90% Tinned Copper Braid - 3.65mm Jacket - Black PE - 4.95mm	
4	HLF 240 Cable	ST01HLF24006	Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Solid Bare Copper - 1.42mm Dielectric- Foamed PE - 3.81mm Inner Shield - Unsealed APA Tape - 3.99mm Outer Shield - 36AWG, 90% Tinned Copper Braid - 4.51mm Jacket - Black PE - 6.10mm	
5	HLF 300 Cable CCA	ST01HLF300AL06	Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Solid Copper Clad Aluminium - 1.78mm Dielectric- Foamed PE - 4.83mm Inner Shield - Unsealed APA Tape - 4.98mm Outer Shield - Copper Clad Aluminium - 5.72mm Jacket - Black PE - 7.62mm	
6	HLF 300 Cable TNCU	ST01HLF300CU06	Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Solid Copper Clad Aluminium - 1.78mm Dielectric- Foamed PE - 4.83mm Inner Shield - Unsealed APA Tape - 4.98mm Outer Shield - Tinned Plated Copper Braiding - 5.72mm Jacket - Black PE - 7.62mm	
7	HLF 400 Cable CCA	ST01HLF400AL06	Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Solid Copper Clad Aluminium - 2.77mm Dielectric- Foamed PE - 7.24mm Inner Shield -sealed APA Tape - 7.42mm Outer Shield - 34AWG, 90% Aluminium Braid - 8.12mm Jacket - Black PE - 10.29mm	
8	HLF 400 Cable TNCU	ST01HLF400CU06	Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Solid Copper Clad Aluminium - 2.77mm Dielectric- Foamed PE - 7.24mm Inner Shield -sealed APA Tape - 7.42mm Outer Shield - 34AWG, 90% TCCA - 8.12mm Jacket - Black PE - 10.29mm	

9	HLF 600 Cable	ST01HLF60006	<p>Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Solid Copper Clad Aluminium - 4.47mm Dielectric- Foamed PE - 11.56mm Inner Shield -sealed APA Tape - 11.76mm Outer Shield - 34AWG, 90% Tinned Copper Braid - 12.47mm Jacket - Black PE - 14.99mm</p>	
10	8DFB Cable	ST018DFB06	<p>Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Bare copper - 2.8mm Dielectric- Foamed PE - 7.8mm Inner Shield - Bonded aluminium foil - 8.0mm Outer Shield - Tinned copper braid(16x9x0.15mm) - 8.6mm Jacket - Black PE - 10.6mm</p>	
11	5DFB Cable	ST015DFB	<p>Coaxial Cable Impedance - 50ohm Colour - Black Inner Conductor- Bare copper - 1.8mm Dielectric- Foamed PE - 5.0mm Inner Shield - Bonded aluminium foil - 5.2mm Outer Shield - Tinned copper braid - 5.7mm Jacket - Black PE - 7.5mm</p>	