



S. NO.	Products	PART NO.	DESCRIPTION	IMAGES
1	0.5 W SMA M DUMMY LOAD 3GHZ	ST04DL05SMM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 0.5watt Connector - SMA M Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	
2	100 W N M DUMMY LOAD 3GHZ	ST04DL100NM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 100watt Connector - N Male Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	
3	10 W N M DUMMY LOAD 3GHZ	ST04DL10NM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 10watt Connector - N Male Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	
4	1 W N M DUMMY LOAD 3GHZ	ST04DL1NM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 1watt Connector - N Male Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	
5	2 W F M DUMMY LOAD 3GHZ	ST04DL2FFM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 2watt Connector - F Male Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	
6	2 W N M DUMMY LOAD 3GHZ	ST04DL2NM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 2watt Connector - N Male Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	
7	50 W DIN M DUMMY LOAD 3GHZ	ST04DL50DINM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 50watt Connector - DIN Male Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	

8	50 W N M DUMMY LOAD 3GHZ	ST04DL50NM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 50watt Connector - N Male Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	
9	5 W DIN M DUMMY LOAD 3GHZ	ST04DL5DINM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 5watt Connector - DIN Male Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	
10	5 W N M DUMMY LOAD 3GHZ	ST04DL5NM03	Impedance - 50ohm Frequency - D-3Ghz VSWR - 1.20 Average Power - 5watt Connector - N Male Application - Microwave Comp. Temp Range - -55°C~+80°C Compliance - ROHS	