








S. NO.	Products	PART NO.	DESCRIPTION	IMAGES
1	2 WAY N F CAVITY SPLITTER 698-2700 MHZ	ST04PS2C69827	Impedance - 50ohm Frequency - 698-2700Mhz VSWR - 1.5 Type - Cavity Max. Power - 200watt Connector - N F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
2	2 WAY N F CAVITY SPLITTER 700-3500 MHZ	ST04PS2C69835	Impedance - 50ohm Frequency - 698-3500Mhz VSWR - 1.5 Type - Cavity Max. Power - 200watt Connector - N F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
3	2 WAY SMA F MICROSTRIP SPLITTER 698-2700 MHZ	ST04PS2M69827	Impedance - 50ohm Frequency - 698-2700Mhz VSWR - 1.5 Type - Microstrip Max. Power - 200watt Connector - SMA F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
4	3 WAY N F CAVITY SPLITTER 698-2700 MHZ	ST04PS3C69827	Impedance - 50ohm Frequency - 698-2700Mhz VSWR - 1.5 Type - Cavity Max. Power - 200watt Connector - N F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
5	3 WAY N F CAVITY SPLITTER 700-3500 MHZ	ST04PS3C69835	Impedance - 50ohm Frequency - 698-3500Mhz VSWR - 1.5 Type - Cavity Max. Power - 200watt Connector - N F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
6	3 WAY N F MICROSTRIP SPLITTER 800-2500 MHZ	ST04PS3M80025	Impedance - 50ohm Frequency - 800-2500Mhz VSWR - 1.5 Type - Microstrip Max. Power - 200watt Connector - SMA F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
7	4 WAY N F CAVITY SPLITTER 698-2700 MHZ	ST04PS4C69827	Impedance - 50ohm Frequency - 698-2700Mhz VSWR - 1.5 Type - Cavity Max. Power - 200watt Connector - N F Compliance - ROHS Temp. Range - - 45°C – +85 °C	

8	4 WAY N F CAVITY SPLITTER 700-3500 MHZ	ST04PS4C69835	Impedance - 50ohm Frequency - 698-2700Mhz VSWR - 1.5 Type - Cavity Max. Power - 200watt Connector - N F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
9	4 WAY N F MICROSTRIP SPLITTER 800-2500 MHZ	ST04PS4M80025	Impedance - 50ohm Frequency - 800-2500Mhz VSWR - 1.5 Type - Microstrip Max. Power - 200watt Connector - SMA F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
10	4 WAY SMA F MICROSTRIP SPLITTER 698-2700 MHZ	ST04PS5M69827	Impedance - 50ohm Frequency - 698-2700Mhz VSWR - 1.5 Type - Microstrip Max. Power - 200watt Connector - SMA F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
11	8 WAY SMA F MICROSTRIP SPLITTER 800-2500 MHZ	ST04PS8M80025	Impedance - 50ohm Frequency - 698-2700Mhz VSWR - 1.5 Type - Microstrip Max. Power - 200watt Connector - SMA F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
12	8 WAY N F MICROSTRIP SPLITTER 800-2500 MHZ	ST04PS8M80025	Impedance - 50ohm Frequency - 800-2500Mhz VSWR - 1.5 Type - Microstrip Max. Power - 200watt Connector - SMA F Compliance - ROHS Temp. Range - - 45°C – +85 °C	