



## H58UB Thermal Receipt Printer



### Product Introduction:

H58 is a well-designed economic printer for common thermal bill printing ,this mold is with solid material,Exquisite workmanship.Transparent cover design, simple and fashion, easy for users to know the paper rolls' Using status,HOP-H58 adopt built-in power supply,not only can save space,but also easy for users to configure and use the printers.It's a very good choice for economical printing.

### Product Features :

Simple and fashion,With solid material,exquisite workmanship.

Easy paper install structure,simple and convenient to operate

Built-in power supply design, to save space and more convenient to configure;

Transparent cover design, the user can know the paper roll's using status anytime;

Support GB18030 big font, easy to print **uncommon characters**

Support multi language print, suitable for users all over the world;

Support download and print LOGO & graphics ;

Support Windows, Linux, Android and IOS system printing.

### Application Area :

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

## Parameters :

Items		Parameters
Print parameters	Printing Method	Thermal Line
	Printing Method	48MM
	Resolution	384dots/Line (8dots/mm, 203dpi)
	Printing Speed	130mm/Second
	Interface Type	USB, USB+Bluetooth(1 to 1),USB+Bluetooth(1 to many)
	Line Spacing	3.75 mm (Can adjust line spacing by command)
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANKcharacter, Font A : 1.5×3.0mm (12×24 点) Font B : 1.1×2.1mm (9×17 点) Simplified/Traditional Chinese : 3.0×3.0mm(24×24 Dots)
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/ Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/P C858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/T haiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251 )/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code : UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 2D bar code : QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clameshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input : AC 100V-240V,50-60Hz
		Output : DC 12V/2A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	4K
	NV Flash	40K
physical characteristics	Weight	590g
	Dimension	185*130*112(MM)
Environment	Working	Temp : 5 ~ 45℃, Humidity : 10 ~ 80%
	Storage	Temp : -10 ~ 50℃, Humidity : 10 ~ 90% (No dew)
Reliability parameter	Print Head Life	100KM (print density≤12.5)
	Cutter Life	MANUAL TYPE

