



HIGH VOLTAGE TESTER 5KV AC DOT 450



- 0 to 5 KV AC variable
- Analogue display
- Protective HT output socket
- Reliable for ISI test
- Selectable leakage current
- Suitable HT probe

Technical Specifications

VOLTAGE RANGE	0 to 5 KV AC (Continuously variable voltage)
CURRENT RANGE	0 to 100 milli amps selectable in three steps of 25,50,100 milli Amps
METER	Analogue moving coil type for voltage and current
ACCURACY	+ / - 5 %
INDICATION	HT ON, OFF, Insulation breakdown
AUDIO BUZZER	Buzzer turns on when HT is on
HT TERMINATION	By HT probe
CONTROLS	HT ON, HT Reset
POWER REQUIREMENT	230 +/-10% VAC, 50 Hz, single phase
CABINET SIZE	19"(W) X 133 (H) X 290 (D) mm
WEIGHT	19.0 Kg Approx
Supplied with HT probes one No, Ground wire, mains cord, spare fuse, and operating manual	

Note: For other configurations/HV output, please contact DOT TECHNOLOGIES

[ClickForBackToTOC](#)

DOT TECHNOLOGIES

(An ISO 9001:2015 Certified Company)

25, Victoria Road, Victoria Layout, Bangalore-560047 INDIA; Email: sales@dottech.in, info@dottech.in; web: www.dottech.in
Phone: +91 8970010661 /+91 7483641565