



HIGH VOLTAGE TESTER 10KV ACDC DOT 457



- 0 to 10KV DC & 0 to 10KV AC
- 3 Digit LED display for KV & m A
- Timer 0 to 5 minutes variable
- Leakage current selectable 100 m A
- HT buzzer indication
- Selection of DC / AC output
- Suitable HT Probe

Technical Specifications

| | |
|--|---|
| VOLTAGE RANGE | 0 to 10 KV AC And 0 to 10 KV DC (Continuously variable voltage) |
| CURRENT RANGE | 0 to 100 milli amps continuously selectable |
| METER | Digital meters for voltage and current indication 3 digits, LED display |
| ACCURACY | +/- 5 % |
| LAMPS | For HT ON, HT OFF |
| HT ON | Audio buzzer and lamp indication |
| HT TERMINATION | HT probe insulated for 20 k V |
| TIMER | 0 to 5 minutes in steps of 30 seconds |
| TEST PASSED | By lamp indication |
| TEST FAILED | By lamp indication |
| CONTROLS | Timer ON, Zero Start, Buzzer ON, HT Warm Lamp, Foot Switch ON, Reset, HT ON, Power ON, AC/DC Select |
| POWER REQUIRED | 230 +/- 10% V AC, 50 Hz, single phase |
| CABINET SIZE | 430 (W) x 170 (H) x 400 (D) in mm {19", 4 U, 400 mm depth} |
| WEIGHT | 37 Kg Approx. / 60Kg with wooden box packing |
| Supplied with HT Probe 2 No, Ground wire, Mains card, spares fuse and comprehensive operating manual | |

Note: For other configurations/HV output, please contact DOT TECHNOLOGIES

[ClickForBackToTOC](#)

DOT TECHNOLOGIES

(An ISO 9001:2015 Certified Company)

25, Victoria Road, Victoria Layout, Bangalore-560047 INDIA; Email: sales@dottech.in, info@dottech.in; web: www.dottech.in
Phone: +91 8970010661 /+91 7483641565