



## DC REGULATED POWER SUPPLY RACK MOUNT CV/CC 19" INCH



- Constant voltage/current
- 3 ½ Digit LED display V, A
- Compact reliable design

MODEL	OUTPUT
4112	0 to 16 V, 2A
4115	0 to 16 V, 10A
4123	0 to 32 V, 2A
4125	0 to 32 V, 10A
4127	0 to 32 V, 30A
4131	0 to 64V, 1A
4133	0 to 64 V, 3A
4135	0 to 64 V, 10A
4137	0 to 128 V, 1A
4141	15 to 300 V, 1A
4143	15 to 300 V, 3A
4158	0 to 15V, 15A

MODEL	OUTPUT
4114	0 to 16 V, 6A
4121	0 to 32V, 1A
4124	0 to 32 V, 5A
4126	0 to 32 V, 20A
4128	0 to 32 V, 40A
4132	0 to 64V, 2A
4134	0 to 64 V, 5A
4136	0 to 64 V, 20A
4139	0 to 128 V, 5 A
4142	15 to 300 V, 2A
4144	15 to 300 V, 5A
4167	0 to 16V, 20A

### SPECIFICATIONS

RIPPLE	0.02% mV r.m.s
LINE REGULATION	+/- 0.01% +/- 9 mV for line voltage variation of +/-10%
LOAD REGULATION	+/- 0.01% +/- 9 mV for no load to full load
METER	2 Digital Meters for Voltage & Current, 3 Digits, LED, Accuracy 0.5%,
PROTECTION	Constant current type for overload and short circuit.
POWER REQ.	230 +/-10% VAC, 50 Hz. 1phase
CABINET SIZE	
4112, 4113,4115,4121, 4123,4131,4133	19"1/2 RACK, 3U, DEPTH 270 (260 W x 133 H x 250 D)
4114,4115,4124, 4125, 4134, 4126, 4127, 4128,4135, 4136,	19" 3U, DEPTH 290 (480 W x 133 H x 290 D)
4139 4141,4142,4143,4144,	19" 6U, DEPTH 320 (480 W x 266 H x 320 D)

The instrument is supplied with mains cord, spare fuse, operating manual

**Note: For other configurations or customized output please contact DOT TECHNOLOGIES**

[ClickForBackToTOC](#)

## DOT TECHNOLOGIES

(An ISO 9001:2015 Certified Company)

25, Victoria Road, Victoria Layout, Bangalore-560047 INDIA; Email: [sales@dottech.in](mailto:sales@dottech.in), [info@dottech.in](mailto:info@dottech.in); web: [www.dottech.in](http://www.dottech.in)  
Phone: +91 8970010661 /+91 7483641565