

DC REGULATED POWER SUPPLY CV/CC RACK MOUNT DUAL OUTPUT 19 inch



- Constant voltage/current
- 31/2 Digit LED display V, A
- Compact reliable design
- Dual Output

MODEL	OUTPUT
4159	0 to 16 V, 2A dual
4160	0 to 16 V, 6A dual
4161	0 to 32 V, 1A dual
4162	0 to 32 V, 2A dual
4164	0 to 32 V, 5A dual
4165	0 to 32 V, 10A dual
4166	0 to 32 V, 20A dual
4172	0 to 64 V, 2A dual

COMMON SPECIFICATIONS

RIPPLE	0.02% mV r.m.s	
LINE REGULATION	+/- 0.01% +/- 9 mV for line voltage variation of +/-10%	
LOAD REGULATION	+/- 0.01% +/- 9 mV for no load to full load.	
METER	4 Digital Meters for Voltage & Current, 3 Digits, LED Accuracy 0.5%	
PROTECTION	Constant current type for overload and short circuit.	
POWER REQ.	230 +/-10% VAC, 50 Hz. 1phase	
CABINET SIZE		
4159,4160,4161, 4162, 4164,4172	19" 3U, DEPTH 320 (480 W x 133 H x 320 D)	
4165, 4166	19" 6U, DEPTH 350 (480 W x 266 H x 350 D)	
The instrument is supplied with mains cord, spare fuse, comprehensive operating manual		

Note: For other configurations or customized output please contact DOT TECHNOLOGIES

ClickForBackToTOC