



DC REGULATED POWER SUPPLY CV/CC RACK MOUNT TRIPLE OUTPUT

19 inch DOT 4152



- Constant voltage/current
- 3 ½ Digit LED display V, A
- Over load, short circuit protection
- Three independent outputs
- Compact reliable design

| MODEL No. | OUTPUT VOLTS/CURRENT |
|-----------|--|
| 4152 | 1) 0 to 32 V, 2A 2) +/- 13.5 to 16 V, 1A 3) 4.5 to 5.5 V, 5A |

COMMON SPECIFICATIONS

| | |
|--|--|
| RIPPLE | 0.02% mV r.m.s |
| LINE REGULATION | +/- 0.01% +/- 9 mV for line voltage variation of +/-10% |
| LOAD REGULATION | +/- 0.01% +/- 9 mV for no load to full load. |
| METER | Out put 1- two Digital Meters for Voltage & Current, 3 Digits, LED Accuracy 0.5%, Out put 2 & 3- One Digital Meters for Voltage selectable |
| PROTECTION | Constant current type for overload and short circuit. |
| POWER REQUIREMENT | 230 +/-10% VAC, 50 Hz. Single phase |
| CABINET SIZE | 19" 3U, DEPTH 320 (480 W x 133 H x 320 D) |
| The instrument is supplied with mains cord, spare fuse, comprehensive operating manual | |

Note: For other configurations or customized output please contact DOT TECHNOLOGIES

[ClickForBackToTOC](#)

DOT TECHNOLOGIES

(An ISO 9001:2015 Certified Company)

25, Victoria Road, Victoria Layout, Bangalore-560047 INDIA; Email: sales@dottech.in, info@dottech.in; web: www.dottech.in
Phone: +91 8970010661 /+91 7483641565