

CINT/BM-260W



Storage Capacity

Face Capacity	1200
Finger Capacity	3000
Card Capacity	2000
Max User	2000
Log Capacity	1,50,000



Face



Finger



RFID



Battery
(Optional)



WiFi



LAN



USB



Access
Control

Features

High-Speed and Accurate Face Identification

Good adaptation for dry, moist and rough fingerprints.

Output relay for door open.

Face, Fingerprint, Card, Password authentication.

Supremely low Electric energy consumption.

Highly reliable and durable.

Communication Interface

Communication	WIFI, TCP/IP, USB
---------------	-------------------

Biometric

Push Data	Yes
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
OS	Linux
Verification time	<=1 second
RF card options	125kHz EM (Standard) / 13.56MHz Mifare (Optional)

Audio/Visual

LCD	2.8" TFT color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand in & out	YES
Relay	YES
Support Exit Reader	Wiegand Reader
	Remote, Push Button, No Touch

Power & Enviroment

Battery	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	175 x 120 x 95 mm



Auto Focus



low light Verification



Long Distance Verification



Accepts Color Finger

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App