

Features

TruVision 10 Port Giga POE Switch

- 10*10/100/1000Mbps ,2Giga @ 2SFP/TP UP Link port
- 250m Distance; Wlan Support
- REALTEK Chipset
- Support IEEE802.3AF/AT
- Whole Power:150W(52V 2.3A)
- All port supported by MDI/MDIX auto flip and self-negotiation
- Supply 8 10/100Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. Power supply reached 30W.



Specifications

Model	PSE-6008-GS
10/100Mbps Copper Ports	8* 10/ 100/1000Mbps Base-TX RJ-45 Auto-MDI/MDI-X ports
1000Mbps Copper Ports	2* 10/100/1000Mbps RJ-45 Auto-MDI/MDI-X ports
SFP/mini-GBIC Slots	2* 1000Base-SX/LX, shared with Port-9~Port-10
Switch Fabric	20 Gbps / non-blocking
Switch Throughput	4.17Mpps @64Bytes
Address Table /Frame Size	8K entries , 9K Bytes
Share Data Buffer	512Kbytes
Flow Control	Back pressure Half-Duplex ,IEEE 802.3x Pause Frame for Full-Duplex
LED	Power (yellow);POE(yellow) 10/100/1000 LINK / ACT (Green)1000 LINK(yellow)
Reset Button	< 5 sec: System reboot > 5 sec: Factory Default
Weight	1.6 kg
Power Requirement	100~240V AC, 50-60 Hz
Power Consumption / Dissipation	150 Watts maximum /510 BTU/hr maximum
PoE Standard	IEEE 802.3af/at Power over Ethernet / PSE
PoE Power Supply Type	End-Span
PoE Power Output	Per Port 52V DC, 350mA~600ma . Max. 30 Watts
Power Pin Assignment	1/2(+), 3/6(-)
PoE Power Budget	130 Watts
Max. number of Class 3 PD	8