

BM-150/ABH-150L

Tri Beam Perimeter Infra-red Sensor

Features

- Passed CE,FCC,ROHS,IP55 certification
- Unique displacement, high power digital filter
- Green environmental protection
- Patent coaxial spherical bifocal precision optical focusing mirror
- Fully functional diagnosis, adaptive environment, and fault locking
- Anti-glare up to 50,000 LUX, built-in automatic adjustment strong light filtering system
- Up and down optical lens can adjust the mechanical design.
- Smart power emission: according to the Environmental conditions to automatically adjust power
- Special-purpose DSP chip, patent multidimensional fault-tolerant, true detection alarm technology
- Adopts the long life, low voltage, small power consumption, solid state relay



Specifications

Model:	BM-150/ABH150L		
Outdoor alert distance:	150m		
Indoor alert distance:	300m		
Beam:	3		
Induction speed:	35-700ms		
Alarm output :	NC & NO	contact rating: AV/DC	30V/0.5mA
Ganged Alarm:	Yes		
Working voltage:	DC 12-24V AC 11-18V		
Working current:	105mA		
Long-life mode:	40mA		
Humidity:	5%-95% (RH)		
Temperature Scope	-25°C~+55°C		
Tamper output:	NC	contact rating: AC/DC	24V/0.5mA
Horizontal angle adjustment:	180° ± 90°		
Vertical angle adjustment:	20° ± 10°		



As a company of innovation, TVS Security reserves the right to change product specifications without notice. For the latest product specifications, visit TVS Security online www.tvsecurity.com or contact your TVS Security sales representative.