

Floor mount overhead door contact with stainless steel armored cable

Overhead Door Magnetic Contact

The 60 series overhead door magnetic contact is for use in the Rigorous environments of Commercial and Industrial installations. The floor mount units are constructed with a low profile heavy cast aluminum housing. The reed switch assembly is fully encased in TVS's exclusive polyurethane potting material to prevent damage due to moisture or humidity.



Easy Installation

A wide operating gap distance of up to 7.5 cm makes installation easy and helps prevent false alarms caused by door movement or damaged and loose fitting doors.

Durability and dependability

High performance magnetic contacts have been designed to facilitate installation and ensure durability and expendability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

High quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.

Standard Features

Miniature, low profile design Stainless steel armored cable for added security, reliability wide working gap for overhead doors. Small size less likely to be damaged by forklifts Optional tamper loop (depending on model)

Specifications

Gap distance (max) 76 mm
Connections 45 cm stainless steel armored cable
Contact NC
Supervised loop No
Dimensions (L x W x H)
Contact 89 x 38 x 11 mm
Magnet 89 x 38 x 38 mm
Color Aluminum
Magnet 1958-L



As a company of innovation, TVS Security reserves the right to change product specifications without notice. For the latest product specifications, visit TVS Security online www.tvssecurity.com or contact your TVS Security sales representative.