

HC-32

Recessed Magnetic Contact Sensor Switch

Features

Recessed stubby press fit magnetic contacts with wire Leads 3/8 in. dia. The HS-32 series stubby press fit Magnetic contact is a 3/8-inch diameter switch designed specifically for applications where space is limited. HS-32's short length makes it ideal for thin framed windows and doors where longer units cannot be used. Press fit ribs on the housing make installation quick and easy.



- Press fit design makes installation easy no screws or glue needed
- Small size perfect for thin-framed windows and doors
- Good for use in vinyl-clad and custom windows
- Ideal for pre-wiring; eliminates forcing switch and pre-wire into the same header hole
- Available wider gap distance helps prevent false alarms caused by loose fitting doors and windows

Specifications

Model	HS-32
Usage	Excellent Recessed Magnetic Contact
Housing	Flame Retardant ABS ,white /brown
Output	N.C
Gap	15 15-25mm available on request
Leads	1007UL24AWG330mm,1007UL22AWG430mm available
Dimension	Φ10*10*18.5mm
Voltage	100VAC/VDC Max.
Power	7.5 W Max.
Current	0.5 A Max.
Package	40sets/PE ,2400sets/box
Gross Weight	20.0KG



As a company of innovation, TVS Security reserves the right to change product specifications without notice. For the latest product specifications, visit TVS Security online www.tvsecurity.com or contact your TVS Security sales representative.