Handheld Particle Counter Model P231



The Airy Technology P231 remote particle counter measures 0.5 µm and 5.0 µm with a flow rate of 1.0 CFM (28.3 LPM). Integration is easy into a real-time monitoring or building management system via Modbus™ RTU or Modbus™ ASCII. The P231 is the smallest remote particle counter in the market and has easy mounting options. The Airy Technology P231 complies with ISO 21501-4 and includes a 2 year limited warranty.

Features & Benefits

- Measures 0.5 μm and 5.0 μm
- 1.0 CFM (28.3 LPM) flow rate
- Measures 2 channels of simultaneous data
- Long life laser diode
- Modbus™ RTU or Modbus™ ASCII outputs
- Concentration limit of 500,000 per ft3
- Complies with ISO 21501-4 and JIS B9921 standards
- Lightweight stainless steel enclosure
- Easy to clean and wipe down





Handheld Particle Counter Model P231





Specifications

Channel Sizes	0.5 µm and 5.0 µm
CHAILLEL 212C3	υ.ο μπι απα ο.υ μπι

Counting Efficiency 50% at 0.5 μ m; 100% for particles > 0.75 μ m (per JIS)

Concentration Limits 500,000 particles / ft3 at 5% coincidence loss

Light Source Long life laser diode

Zero Count Level <1 count / 5 minutes (per JIS B9921)
Size Resolution <15% at 0.5 μm (per ISO 21501-4)

Flow Rate 1.0 CFM (28.3 LPM)
Flow Control Critical orifice

Vacuum Requirements External vacuum >15" (38.1 cm) of Hg

Calibration NIST traceable

Sample Probe/Tubing Isokinetic sampling probe

Communication Interface Modbus™ RTU or Modbus™ ASCII outputs (specified upon order)

Power 9-30 VDC

Dimensions (L x W x H) 1.8" x 3.7" x 1.5" (4.5 cm x 9.3 cm x 3.8 cm) does not include probes

Weight 0.62 lb (0.28 kg)

Standards ISO 21501-4 and JIS B9921

Warranty 2 year limited warranty

Operating Conditions 5° to 35°C 20% to 95%RH non-condensing Storage Conditions -20° to 50°C Up to 98%RH non-condensing Included Accessories Isokinetic sampling probe and user manual

Optional Accessories Purge filter, data cable, vacuum and sample tubing



