

STOCK ORDER PICKER (BATTERY OPERATED)



Standard equipment

- ◆ Controller temperature protection
- ◆ Proportional controls
- ◆ Battery charge indicator
- ◆ Emergency stop button
- ◆ Emergency lowering system
- ◆ Can Bus Technology
- ◆ Charger protection
- ◆ Overload limited
- ◆ Low voltage alarm
- ◆ Safety brackets

Characteristic

- ◆ The light weight and maneuverability make it convenient to use in supermarket and warehouse.
- ◆ Zero-turn radius and compact design (1.53m×0.70m) provide access in and around confined work areas.
- ◆ On-board diagnostic help operators troubleshoot on the fly and make adjustments in the field to maximize uptime.



Parameter table

Model	FSEP3-2.7	FSEP3-3.3	FSEP3-4.0	FSEP3-4.5
Loading Capacity	300Kg	300Kg	300Kg	300Kg
Max. Platform Height	2.70m	3.30m	4.00m	4.50m
Max. Machine Height	4.12m	5.00m	5.40m	6.00m
Platform Size	600*640mm	600*640mm	600*640mm	600*640mm
Stowed Length	1.53m	1.53m	1.62m	1.62m
Stowed Width	0.70m	0.70m	0.70m	0.70m
Stowed Height	1.83m	2.13m	1.84m	2.00m
Min. Turning Radius	1600mm	1600mm	1600mm	1600mm
Max. Climbing Capacity	15%-20%	15%-20%	15%-20%	15%-20%
Ground Clearance	40mm	40mm	40mm	40mm
Driving Motor	2*24V/0.4Kw	2*24V/0.4Kw	2*24V/0.4Kw	2*24V/0.4Kw
Lift Motor	24V/1.6Kw	24V/1.6Kw	24V/1.6Kw	24V/1.6Kw
Battery	2*12V/150Ah	2*12V/150Ah	2*12V/150Ah	2*12V/150Ah
Charger	24V/15A	24V/15A	24V/15A	24V/15A
Overall Weight	430Kg	450Kg	660Kg	680Kg

