

ALUMINIUM VERTICAL TWIN MAST LIFT



Since 1907



Standard equipment

- ◆ Leveling outrigger device
- ◆ Two controllers operation
- ◆ Emergency stop button
- ◆ Emergency lowering system
- ◆ Overloading limited
- ◆ Battery charge indicator
- ◆ Limit switch
- ◆ Level instrument



Parameter table

Model	GTWY802	GTWY1002	GTWY1202
Capacity (kg)	300	250	200
Max Platform height H1(m)	8	10	12
Max working height H2 (m)	10	12	14
Platform size (m)	1.28X0.66	1.54X0.66	1.54X0.66
Overall length A (m)	1.53	1.79	1.79
Overall width B (m)	0.82	0.82	0.87
Overall height H3(m)	1.81	1.86	2.03
Outrigger Footprint(L/W)	1.65X1.66	2.13X1.89	2.13X1.94
Ground clearance (m)	0.08	0.08	0.08
Wheelbase	1.18	1.44	1.44
Front wheels size (inch)	8	8	8
Rear wheel (inch)	8	8	8
Battery	2-12V/65Ah	2-12V/65Ah	2-12V/65Ah
Integrated charger	12V/15A	12V/15A	12V/15A
Lifting motor (AC)	110-230V/1.5KW	110-230V/1.5KW	110-230V/1.5KW
Lifting motor (DC)	12V/1.5KW	12V/1.5KW	12V/1.5KW
Lifting time (S)	62	70	75
Lowering time (S)	43	46	54
Self weight (kg)	630(AC) 670(DC)	730(AC) 770(DC)	825(AC) 865(DC)

