



Expanding Digital Technologies



( Optional : 2/4/8 Out )









## DC NODE DLX - OPM

MODEL NO. 2051/2055/2059 - ( 7VDC - 40VDC )

### Description :-

Optivision Model no.2051/2055/2059 is 7VDC - 40VDC operated, low power consumption with high-output, high-performance, full-featured CATV optical node designed very latest SMD Technology to provide reliable deliver a full performance of multiplexed video. The unit is constructed with high quality components to enable it to meet or exceed its performance. It has External Fuse so that customer can control the Input-Output power Supply. This unit can be operate via multi-power supply i.e : POC /Solar-Pannel/ 12VDC Power Adaptor / 35VDC Power supply. The unit have powder coated housing for rust free. This node have OPM ( Optical Power Meter ).

|  |   |  |   |  |
|--|---|--|---|--|
| <br>Wave length<br>1200nm - 1600nm  | <br>RF Output Level<br>115/110/105dBµv | <br>ECO<br>FRIENDLY                   | <br>ATTENUATION<br>-20dB | <br>High Responsive<br>Optical Module |
| <br>Optical Input<br>+2dBm ~ -16dBm | <br>Linear<br>1000MHz                  | <br>POC/35VDC/ADAPTOR<br>7VDC - 40VDC | <br>GaAs IC<br>MODULE    | <br>HD + DIGITAL<br>READY             |