



SHREE TRADING COMPANY

SINCE : 1998

DSKS THERMOX-X - SUPERIOR SILICON CARBIDE CRUCIBLES RESIN BONDED SILICON CARBIDE CRUCIBLES For Furnace Type – Lift out and Bale out

Sr. No.	Model	Height (mm)	Outside Diameter		Brimful Water Capacity (Kg)	Approx. Brass Melting Capacity (Kg)
			Top	Bottom		
			(mm)	(mm)		
1	DSKS-A-18	275	222	150	5.09	38.9
2	DSKS-A-20	290	230	150	6.1	45
3	DSKS-A-25	305	230	150	6.9	51
4	DSKS-A-30	330	282	192	10	75
5	DSKS-A-35	360	282	192	11	82.5
6	DSKS-A-40	385	282	192	12	90
7	DSKS-A-60	390	330	230	16	120
8	DSKS-A-80	415	330	230	18.6	140
9	DSKS-A-90	445	330	230	19.1	143.5
10	DSKS-A-100	445	355	245	23	172
11	DSKS-A-110	475	355	245	24.5	184
12	DSKS-A-120	460	375	255	26	195
13	DSKS-A-130	480	375	255	26.8	201
14	DSKS-A-160	455	385	230	27.5	206
15	DSKS-A-175	475	385	230	28.8	216
16	DSKS-A-180	500	385	230	30.6	230
17	DSKS-A-185	540	385	230	34	255
18	DSKS-A-186	570	385	230	36.8	276.55
19	DSKS-A-187	590	385	230	38.5	289.33
20	DSKS-A-188	610	385	230	39.9	299.85
21	DSKS-A-190	655	385	230	43.3	325.4
22	DSKS-A-200	502	400	290	33.5	252
23	DSKS-A-201	540	400	290	37	278
24	DSKS-A-207	620	385	230	40.8	306.61

For Furnace Type – Lift out and Bale out

Sr. No.	Model	Height (mm)	Outside Diameter		Brimful Water Capacity (Kg)	Approx. Brass Melting Capacity (Kg)
			Top	Bottom		
			(mm)	(mm)		

SHREE TRADING COMPANY

Address : Shiv-Vaibhav, Plot No 25 A/2, B/h. Kishor Pan, Anantwadi, Dist. Bhavnagar Gujarat, India
+91 278 252 2235 / + 91 9824246823 / +91 9909795005
E-mail : shreeintel1998@yahoo.com www.shreeintel.com



SHREE TRADING COMPANY

SINCE : 1998

25	DSKS-A-210	545	430	260	38.29	287
26	DSKS-A-216	575	400	290	40	300.6
27	DSKS-A-225	570	430	260	40.6	305
28	DSKS-A-234	610	400	290	43.12	324.05
29	DSKS-A-240	595	430	260	43.2	324
30	DSKS-A-250	640	430	260	46.1	346
31	DSKS-A-251	560	455	250	43	323
32	DSKS-A-255	590	455	250	48	361
33	DSKS-A-260	665	430	260	48.9	367
34	DSKS-A-265	620	455	250	49	369
35	DSKS-A-280	640	455	250	50.2	377
36	DSKS-A-300	565	430	260	43.14	324.2
37	DSKS-A-325	590	485	280	55.6	417.83
38	DSKS-A-351	635	485	280	59.5	447
39	DSKS-A-355	670	485	280	73	551
40	DSKS-A-365	695	485	280	75	569
41	DSKS-A-375	720	485	280	78	587
42	DSKS-A-380	745	485	280	80	601
43	DSKS-A-400	680	545	315	89	669
44	DSKS-A-405	710	545	315	91	684
45	DSKS-A-500	690	575	355	94.5	710
46	DSKS-A-510	720	575	355	98	735
47	DSKS-A-555	766	575	355	104	781
48	DSKS-A-610	801	575	355	116	871
49	DSKS-A-650	801	581	345	124	931
50	DSKS-A-675	810	581	345	126	953
51	DSKS-A-710	830	581	345	130	970
52	DSKS-A-715	870	581	345	133	1000

**DSKS THERMOX-X - SUPERIOR SILICON CARBIDE CRUCIBLES
RESIN BONDED SILICON CARBIDE CRUCIBLES
For Furnace Type – Bale out Furnace**

Sr. No.	Model	Height (mm)	Outside Diameter		Brimful Water Capacity (Kg)	Approx. Al Melting Capacity (Kg)
			Top	Bottom		
			(mm)	(mm)		
1	DSKS-B-164	310	530	315	26.1	63

SHREE TRADING COMPANY

Address : Shiv-Vaibhav, Plot No 25 A/2, B/h. Kishor Pan, Anantwadi, Dist. Bhavnagar Gujarat, India
+91 278 252 2235 / + 91 9824246823 / +91 9909795005
E-mail : shreeintel1998@yahoo.com www.shreeintel.com



SHREE TRADING COMPANY

SINCE : 1998

2	DSKS-B-166	405	530	315	45.2	110
3	DSKS-B-167	455	530	315	52.3	126
4	DSKS-B-168	500	530	315	59.8	145
5	DSKS-B-171	605	530	315	75	182
6	DSKS-B-202	505	616	355	80	194
7	DSKS-B-302	632	616	355	110	267
8	DSKS-B-401	702	616	355	124	301
9	DSKS-B-402	820	616	355	147	357
10	DSKS-B-403	850	616	355	154	374.22
11	DSKS-B-502	900	616	355	163.5	397.31
12	DSKS-B-248	750	780	460	222	540
13	DSKS-B-263	900	780	460	255	620
14	DSKS-B-264	1050	780	460	306	745

DSKS THERMOX-X - SUPERIOR SILICON CARBIDE CRUCIBLES RESIN BONDED SILICON CARBIDE CRUCIBLES For Furnace Type – Tilting Furnace

Sr. No.	Model	Height (mm)	Outside Diameter		Brimful Water Capacity (Kg)	Approx. Brass Melting Capacity (Kg)
			Top	Bottom		
			(mm)	(mm)		
1	DSKS-T-6	730	438	295	61.80	516.00
2	DSKS-T-8	805	440	295	69.60	581.00
3	DSKS-T-10	950	440	295	84.20	704.00

For Furnace Type – Tilting Furnace

Sr. No.	Model	Height (mm)	Outside Diameter		Brimful Water Capacity (Kg)	Approx. Brass Melting Capacity (Kg)
			Top	Bottom		
			(mm)	(mm)		
1	DSKS-T-175	475	385	230	25.3	190
2	DSKS-T-750	565	435	250	32.7	246
3	DSKS-T-510	720	575	355	98	736.47
4	DSKS-T-400	620	385	230	34.9	262.27
5	DSKS-T-355	670	485	280	61.3	460.5
6	DSKS-T-843	680	430	255	45.5	380
7	DSKS-T-982	805	440	295	66	496
8	DSKS-T-12	950	440	295	80	670
9	DSKS-T-89	801	575	355	101.5	762

SHREE TRADING COMPANY

Address : Shiv-Vaibhav, Plot No 25 A/2, B/h. Kishor Pan, Anantwadi, Dist. Bhavnagar Gujarat, India
+91 278 252 2235 / + 91 9824246823 / +91 9909795005
E-mail : shreeintel1998@yahoo.com www.shreeintel.com



SHREE TRADING COMPANY

SINCE : 1998

For Furnace Type – Tilting Furnace

Sr. No.	Model	Height (mm)	Outside Diameter		Brimful Water Capacity (Kg)	Approx. Al Melting Capacity (Kg)
			Top	Bottom		
			(mm)	(mm)		
1	DSKS-T-287	605	530	315	59.7	145
2	DSKS-T-387	632	616	355	93	226
3	DSKS-T-412	801	616	355	131	319
4	DSKS-T-587	900	780	460	226.3	549
5	DSKS-T-264	1050	780	460	248	602

STAND - ACCESSORIES

S N o	Type	Height	Outside Diameter		Applicable for Crucible Models		
			Top OD	Bottom OD	ARC	BRC	TRC
1	DSKS-R-284/125	125	284	230	160, 175, 180, 200, 205, 230, 250, 255, 325		175, 400
2	DSKS-R-311/125	125	311	250	300, 325, 351, 355, 375, 750, 335, 351, 400, 405	166, 167, 168, 171	10, 12, 14, 287
3	DSKS-R-362/125	125	362	250	500, 510, 555, 610, 710, 715	202, 302, 401, 402	89, 387, 412
4	DSKS-R-362/175	175	362	250	500, 510, 555, 610, 710, 715	202, 302, 401, 402	89, 387, 412
5	DSKS-R-362/200	200	362	250	500, 510, 555, 610, 710, 715	202, 302, 401, 402	89, 387, 412
6	DSKS-R-427/115	115	427	425		248, 263, 264	587, 650
7	DSKS-R-427/165	165	427	425		248, 263, 264	587, 650
8	DSKS-R-427/215	215	427	300		248, 263, 264	587, 650
9	DSKS-R-361-50	50	361	360			
10	DSKS-R-311-50	50	311	310			

Note : Height of all type of stands can be increased as per order or requirement.

SHREE TRADING COMPANY

Address : Shiv-Vaibhav, Plot No 25 A/2, B/h. Kishor Pan, Anantwadi, Dist. Bhavnagar Gujarat, India
 +91 278 252 2235 / + 91 9824246823 / +91 9909795005
 E-mail : shreeintel1998@yahoo.com www.shreeintel.com