

CONTACT RESISTANCE METER

Model : QCRM100

Application:

- Circuit Breaker
- Shunts
- Component Manufacturer
- Isolators
- Busbars
- Current Transformer Manufacturer
- Cables and Joints
- College Laboratories

Features

- True Four Terminal Measurement
- 100 Amp DC Current Max
- 3.5 Digit LCD display
- 0.1uOhm resolution
- Fast Response time
- Builtin Thermal Printer
- Builtin memory for 100 results
- Data Download via RS232 / USB port



Range	Resolution	Test Current	Accuracy
199.9 $\mu\Omega$	0.1 $\mu\Omega$	100A	$\pm 0.5\%$ of rdg ± 3 Digits
1999 $\mu\Omega$	1 $\mu\Omega$	100A	$\pm 0.5\%$ of rdg ± 3 Digits

Technical Specification

Display	: 20 X 4 Backlite LCD Display
Power Supply	: 230V AC, 50Hz, 1 Phase
Operating Temp	: 5 deg C to 45 deg C
Temp Coefficient	: 50 PPM



Standard Accessories

- 3m long probe set
- C clamps
- Mains Cord
- User Manual, Datadownload CD
- Master Earthing Cable

Simplified Measurements Solutions



QUADRANT MEASUREMENTS Pvt. Ltd.

Works : D 51, MIDC, Satpur, Nashik, Maharashtra, INDIA.
Email : sales@quadrantmeasurements.com
Website : www.quadrantmeasurements.com

Simplified Measurements Solutions