

SAB CLASSIC - EXTERNAL CALIBRATION

FEATURES :-

- * Single Touch Key External calibration, ensures the highest accuracy at the press of a key.
- * **Support:** Weighing, Counting, Percentage, Animal Weighing. Optional: Density measurement
- * 18 standard units, with all-character mark.
- * Strong anti-shaking monolithic electromagnetic for highest accuracy.
- * Standard 1500V isolation USB port, ease to connect with PC.
- * User selectable filter, stability indicator and auto-zero tracking for use in difficult environment.
- * Large, sturdy and nearly frameless, all-glass draft shield chamber for optimal viewing of weighing chamber.
- * The draft shield doors and all stainless steel parts of the weighing chamber base are easy to remove in just a few steps for cleaning.
- * Backlit, high-contrast display with 15 mm digits; exceptionally easy to read under any room lighting conditions.



Option Accessories : Density kit, Printer, software, Test weights .

MODEL	CAPACITY [G]	RESOLUTION [G]	PAN [MM]	REPEATABILITY [G]	LINEARITY [G]	RESPONSE TIME [SEC.]
EXTERNAL CALIBRATION						
SAB124CL	120	0.0001	Ø 90	± 0.0001	± 0.0002	<3
SAB224CL	220	0.0001	Ø 90	± 0.0001	± 0.0002	<3
SAB223CL	220	0.001	Ø 110	± 0.001	± 0.0015	<3
SAB323CL	320	0.001	Ø 110	± 0.001	± 0.0015	<3
SAB423CL	420	0.001	Ø 110	± 0.001	± 0.0015	<3
SAB523CL	520	0.001	Ø 110	± 0.002	± 0.002	<3
SAB623CL	620	0.001	Ø 110	± 0.002	± 0.002	<3