

## Kopal

### Copper Based High Performance Antiseize Compound

#### Benefits :

- Reduces friction and thereby reduces wear in high pressure sliding surfaces.
- Prevents seizures at high temperatures.
- Eases dismantling and assembling during installation and maintenance.
- Prevents scuffing, pick up and seizures during wearing in.
- Saves threaded parts from galling, distortion and breaking.
- Guards against rust and corrosion.
- Resists fresh and salt water corrosion.
- Low co-efficient of friction.
- Meets 'break away' torque requirements of MIL-A-907E.
- Good brushability.

#### Applications :

- For slow moving and high load applications.
- For high temperature and corrosive atmospheres.
- For gears, racks, pinions, spline shafts, plain bearings, pivot joints, studs, bolts, nuts & other threaded parts.
- As a Live-Ring lubricant in cement plants.
- Industries include Engineering, Refinery, Cement, Steel, Sugar, Chemicals, Petrochemicals, Textiles, Windmills, Mining, Offshore drilling and many others.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Smooth Paste
Colour	Visual	–	Copper
NLGI Grade	–	–	# 2/1
Worked Penetration	ASTM D-217	0.1 mm	290 – 310
Four Ball Weld Load	ASTM D-2596	N	4000
Copper Strip Corrosion Test	ASTM D-4048	rating	1a
Surface Area Coverage [approx.]	*CTM	m <sup>2</sup> /kg.	45
Solid Lubricant	–	–	Copper
Operating Temperature Range			
Base Oil	–	°C	-30/+150
Solid Lubricants	–	°C	-30/+1100

\*CTM=Corporate Test Method

**Note** : For continuous temp. above 650°C, users are advised to carry out pretests before use.

**Caution** : Do not use as a bearing grease

Marginal variation in shade can be expected from batch to batch . The colour has no effect on the lubricating properties of the product.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice

[REV.11 / 01.04.19]

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

**Anand Engineers Pvt Ltd.** 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com