

**GP-PR80**



**Features :**

- Heavy Duty Thermal Printer**
- 150 KM Head Reliability**
- Built-in Speaker for KOT Buzzer**
- Japanese Head**
- Logo Printing**



Catering



Garment



Retail

**Specification**

Printing Method	Thermal Line	
Resolution	8 dots/mm(203 dpi), 576 dots/line	
Paper Type	Normal Thermal Paper	
Printing Speed	200 mm/s	
Character Set	ASCII, GB18030(Chinese), BIG5, Codepage	
Print Font	Font A: 12x24; Font B: 9x17	
Self-defined Character	Yes	
Barcode	1D	UPC-A, UPC-E, EAN-13, EAN-8, CODE39 · ITF25, CODEBAR, CODE128
	2D	PDF417, QR CODE, DATA MATRIX
Interface	USB/USB+Ethernet	
Cash Drawer Control	DC24V,1 A; 6 PIN RJ-11 socket	
Power Supply (Adapter)	DC24V±10%, 2A	
TPH	150KM	
Effective Printing Width	72 mm/48mm	
Paper Width	79.5±0.5mm/57.5±0.5mm	
Paper Thickness	0.06-0.08mm	
Paper Size	Max 80 mm×Ø80mm/Max 58 mm×Ø80	
Auto Cutter	1,500,000 cuts	
Driver	Windows/JPOS/OPOS/Linux/Android	
Operating Temp/Humidity	0 ~ 50°C /10 ~ 80%	
Storage Temp/Humidity	-20~60°C /10%~90%	
Dimension	179mm×152mm×118mm(LxWxH)	

